

UTP Cat5e Box (PVC) 305mtr

Product Code : 1101-03003 Conductor : 24AWG Bare Solid Copper Insulation : HDPE, FRPE, 100%FEP Jacket : PVC Color : Gray



勝 特 力 材 料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Application :

Voice
ISDN
10Base T(IEEE 802.3)
Fast Ethernet(IEEE802.3)
100Vg-AnyLAN(IEEE 802.12)
Token Ring(IEEE 802.5)
TP-PMD(ANSI X3T9.5)
100Base-T Ethernet(IEEE 802.3u)
155/622 Mbps ATM
1000Base-T
550 MHz Broadband video

Product Electrical Characteristics:

Impedance:100±15 ohms
Resistance Unbalance 100m: 5% max.
Mutual Capacitance, max. nf/ 100m: 5.6
DC Resistance, max. ohms/100m: 9.38
Capacitance Unbalance(Pair to Ground):330pf/ 100m max.

Industry Standard

UL, ETL VerifiedTIA/EIA 568B.2
ISO/IEC 11801

Cable Data:

No. of Pairs: 4
Jacket Color : Gray
Insulation Thickness: 0.195±0.01mm
Nom.O.D.: 5.0±0.2mm
Flame Rating: CM