


Overall Foil/Braid Shield

Computer Cables for EIA RS-232 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Nominal OD		Nominal DCR		Nominal Capacitance				
					Ft.	m	Lbs.	kg	Inch	mm	Cond.	Shield	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m	
22 AWG Stranded (7x30) Tinned Copper Conductors • Overall Beldfoil® (100% Coverage) + Tinned Copper Braid Shield (65% Coverage)																	
Semi-rigid PVC Insulation • Chrome PVC Jacket																	
 Z-Fold®	9939	NEC:	3	See	100	30.5	3.6	1.6	.202	5.13	14.7Ω/M'	6.2Ω/M'	37	121	67	220	
		CMG		Chart 1	500	152.4	14.0	6.4			48.2Ω/km	20.3Ω/km					
		CEC:		(Tech Info Section)	1000	304.8	27.0	12.3									
			CMG FT4														
	9940	NEC:	4	See	100	30.5	4.0	1.8	.215	5.46	14.7Ω/M'	5.0Ω/M'	37	121	67	220	
		CMG		Chart 1	500	152.4	16.5	7.5			48.2Ω/km	16.4Ω/km					
		CEC:		(Tech Info Section)	1000	304.8	32.0	14.5									
			CMG FT4														
	9941	NEC:	5	See	100	30.5	4.2	1.8	.230	5.84	14.7Ω/M'	7.1Ω/M'	37	121	67	220	
		CMG		Chart 1	500	152.4	19.0	8.6			48.2Ω/km	23.3Ω/km					
		CEC:		(Tech Info Section)	1000	304.8	38.0	17.3									
			CMG FT4														
9942	NEC:	6	See	100	30.5	4.7	2.1	.245	6.22	14.7Ω/M'	7.9Ω/M'	35	115	63	207		
	CMG		Chart 1	500	152.4	22.0	10.0			48.2Ω/km	25.9Ω/km						
	CEC:		(Tech Info Section)	1000	304.8	43.0	19.5										
		CMG FT4															
9943	NEC:	7	See	100	30.5	5.0	2.3	.245	6.22	14.7Ω/M'	7.0Ω/M'	35	115	63	207		
	CMG		Chart 1	500	152.4	23.5	10.8			48.2Ω/km	23.0Ω/km						
	CEC:		(Tech Info Section)	1000	304.8	46.0	20.9										
		CMG FT4															
9944	NEC:	8	See	100	30.5	5.5	2.5	.260	6.60	14.7Ω/M'	6.0Ω/M'	35	115	63	207		
	CMG		Chart 1	500	152.4	26.0	11.8			48.2Ω/km	19.7Ω/km						
	CEC:		(Tech Info Section)	1000	304.8	52.0	23.6										
		CMG FT4															
9945	NEC:	9	See	100	30.5	6.1	2.8	.280	7.11	14.7Ω/M'	5.1Ω/M'	35	115	63	207		
	CMG		Chart 1	500	152.4	28.5	12.9			48.2Ω/km	16.7Ω/km						
	CEC:		(Tech Info Section)	1000	304.8	57.0	25.9										
		CMG FT4															
9946	NEC:	10	See	100	30.5	6.6	3.0	.300	7.62	14.7Ω/M'	4.6Ω/M'	35	115	63	207		
	CMG		Chart 1	500	152.4	31.5	14.3			48.2Ω/km	15.1Ω/km						
	CEC:		(Tech Info Section)	1000	304.8	62.0	28.1										
		CMG FT4															
9947	NEC:	15	See	100	30.5	8.7	4.0	.340	8.64	14.7Ω/M'	4.1Ω/M'	35	115	63	207		
	CMG		Chart 2R	500	152.4	42.5	19.3			48.2Ω/km	13.5Ω/km						
	CEC:		(Tech Info Section)	1000	304.8	83.0	37.7										
		CMG FT4															
9948	NEC:	25	See	100	30.5	13.3	6.0	.410	10.41	14.7Ω/M'	3.1Ω/M'	35	115	63	207		
	CMG		Chart 2R	500	152.4	66.5	30.2			48.2Ω/km	10.2Ω/km						
	CEC:		(Tech Info Section)	1000	304.8	132.0	59.9										
		CMG FT4															
9949	NEC:	37	See	100	30.5	16.1	7.3	.460	11.68	14.7Ω/M'	2.7Ω/M'	35	115	63	207		
	CMG		Chart 2R	500	152.4	87.5	39.7			48.2Ω/km	8.9Ω/km						
	CEC:		(Tech Info Section)	1000	304.8	180.0	81.7										
		CMG FT4															
9950	NEC:	50	See	100	30.5	25.2	11.4	.555	14.10	14.7Ω/M'	2.3Ω/M'	35	115	63	207		
	CMG		Chart 2R	500	152.4	118.0	53.6			48.2Ω/km	7.5Ω/km						
	CEC:		(Tech Info Section)	1000	304.8	238.0	108.1										
		CMG FT4															

DCR = DC Resistance

*Capacitance between conductors.

**Nominal capacitance conductor to conductor and shield.

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)