


CABLE NAME		UL1422 24AWG(1/0.50T)		CONSTRUCT				
ITEM		SPECS		<div>Insulation Conductor</div>				
CONDUCTOR	Norm. Area.		24AWG					
	Material		Tinned copper					
	Size		1/0.50+/-0.008mm					
	O.D(Ref)		0.50mm					
INSULATION	Material		PVDF(-40--125℃)		COLOR			
	Min. Average Thickness		0.25mm					
	Min. Thickness		0.23mm		BY ORDER			
	O.D		1.00±0.10mm					
					MARKING			
					REMARK			
				Referance standardUL 758, UL 1581				
ELECTRICAL DATA		PHYSICAL PROPERTIES		UNITPOWER				
<div>1.Rated temperature:125℃ 2.Rated voltage:150V 3.Max. resistance of conductor(20℃):89.39 Ω /km 4.Voltage-withstand test:2.0kV/1min.</div> <div>勝特力材料 886-3-5773766 勝特力电子(上海) 86-21-34970699 勝特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw</div>		<div>1.Tensile strength:≥10.3N/mm² Elongaion:≥150% Aged(125±2℃×48h) Percent of tensile strength:≥70% Percent of elongation:≥65% 2.Flammability test:passes FT1.</div>		SPECS SHEET				
				APPROVED	LIHUI	CUSTOMER		
				CHECKED	LINDA	PART. NO.	1422-24	
				DRAWN	LINDA	DATE	2013.03.13	