
勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
胜特力电子(上海) 86-21-34970699
胜特力电子(深圳) 86-755-83298787
http://www.100y.com.tw

AD-A8A8-A1	**SMA Jack To SMA Jack** **18GHz VSWR 1.2**	**50Ω**



Parts	Material	Plating (Micro-inch)
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator	Teflon	
Body	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20

Weight: 2.14 g

This part number complies with RoHS.
Notice: JYEBAO reserves the right to make modifications deemed appropriate.

AD-A8A8-A1	**SMA Jack To SMA Jack 18GHz VSWR 1.2**

Interface	
Standard	MIL-STD-348B
Mechanically compatible with	2.92 & 3.5


Electrical Data	
Impedance	50Ω
Frequency Range	DC To 18GHz
VSWR	≦1.2 (DC To 18GHz)
Insertion Loss	≦0.04 x $\sqrt{}$f(GHz) dB
Insulation Resistance	≧5000MΩ
Dielectric Withstanding Voltage (at sea level)	1500 V rms
Working Voltage (at sea level)	500 V rms

Mechanical Data	
Recommended Coupling Nut Torque	4 in-lbs
Coupling Proof Torque	5.3 in-lbs
Contact Captivation-axial	≧6.1 lbs
Durability (mating)	≧100

Environmental Data	
Temperature Range	-65°C to +165°C
Thermal Shock	MIL-STD-202, Method 107, Condition B
Moisture Resistance	MIL-STD-202, Method 206
Corrosion	MIL-STD-202, Method 101, Condition B
RoHS	Compliant

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

AD-A8A8-A1



勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
胜特力电子(上海) 86-21-34970699
胜特力电子(深圳) 86-755-83298787
http://www.100y.com.tw