ADS-A8A8-P2	SMA jack to SMA jack 2 hole flange 18GHz VSWR 1.2	50Ω



Parts	Material	Plating (Micro-inch)
Body	Stainless Steel	Passivated
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator	Teflon	

ADS-A8A8-P2	SMA Jack to SMA Jack 2 Hole Flange 18GHz VSWR 1.2

Interface

Standard	MIL-STD-348B
Mechanically compatible with	2.92 & 3.5

Electrical Data

Impedance	50Ω
Frequency Range	DC To 18GHz
VSWR	≦1.2 (DC To 18GHz)
Insertion Loss	≦0.04 x $\sqrt{}$f(GHz) dB
Insulation Resistance	≧5000MΩ
Dielectric Withstanding Voltage (at sea level)	1500 V rms
Working Voltage (at sea level)	500 V rms

Mechanical Data

Recommended Coupling Nut Torque	7 to 9.5 in-lbs
Coupling Proof Torque	15 in-lbs
Contact Captivation-axial	≧6.1 lbs
Durability (mating)	≧500

Environmental Data

Temperature Range	-65°C to +165°C
Thermal Shock	MIL-STD-202, Method 107, Condition B
Moisture Resistance	MIL-STD-202, Method 206
Corrosion	MIL-STD-202, Method 101, Condition B
RoHS	Compliant

ADS-A8A8-P2



勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
胜特力电子(上海) 86-21-34970699
胜特力电子(深圳) 86-755-83298787
http://www.100y.com.tw