
SMA-KK1 母-母 18G

163147	SMA-KK1-轉接器-18G	高頻測試轉接器 SMA 母對母 18G

SMA(FEMALE)-SMA (FEMALE)	**SMA-KK1**



*Dimensions are in mm

Configuration

Connector 1 Type	SMA Female
Connector 1 Impedance	50 Ohms
Connector 1 Polarity	Standard
Connector 2 Type	SMA Female
Connector 2 Impedance	50 Ohms
Connector 2 Polarity	Standard
Connector Mount Method	None
Adapter Body Style	Straight

Electrical Specifications

Frequency	DC to 18 GHz
Insertion Loss (dB)	≤ 0.1 xSqt.(f_GHz)
VSWR /Return Loss	1.25 to 18 GHz


Materials Information

Center Contact	CuBe Gold Plated
Outer Contact	Brass Gold Plated
Body	Brass Gold Plated
Dielectric	PTFE


Environmental Data

Temperature Range	-55°C to +165°C
2002/95/EC(RoHS)	Compliant


While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.




SMA-JJ




SMA-JK



SMA-KK



SMA-KK1



SMA-KK1