

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 08/11/07'	~	



勝 特 力 材 料 886-3-5753170
胜特力电子(上海) 86-21-34970699
胜特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw




N:HALF OF CONTACTS

18		
19		
20		
21		
22		
23		
24		
25		

10		
11		
12		
13		
14		
15		
16		
17		

TYPE	DIM A	DIM B
1	3.70	2.10
2	3.50	3.50
3	4.00	2.50
4	3.00	2.30
5	2.50	2.00
6	3.30	2.50
7		
8		
9		



RECOMMEND PCB LAYOUT(TOLERANCE=±0.05)

NOTES:

1. MATERIAL
   - 1.1 INSULATOR:THERMOPLASTIC(UL 94V-0).
   - 1.2 CONTACT MATERIAL:COPPER ALLOY.
2. SPECIFICATION
   - 2.1 CURRENT RATING:1.0 Amp.
   - 2.2 INSULATION RESISTANCE:500MΩ Min.
   - 2.3 DIELECTRIC WITHSTANDING:300VAC.
   - 2.4 CONTACT RESISTANCE:20mΩ Max.
   - 2.5 OPERATING TEMPERATURE:-40°C TO+105°C.
3. PRODUCT NUMBER CODE:

DS1031-06 - X X X X X X X

- DIM.A B TYPE
  - 1: TYPE 1
  - 2: TYPE 2
  - 3: TYPE 3
  - 4: TYPE 4
- HOUSING DIM(DIM. C, W)
  - 1: C=1.00mm W=3.4mm
  - 2: C=1.50mm W=3.4mm
  - 3: C=1.70mm W=3.0mm
  - 4: C=2.00mm W=3.0mm
  - 5: C=2.50mm W=3.0mm
- MOUNTING TYPE
  - V: VERTICAL TYPE
- HOUSING COLOR
  - B:BLACK
- CONTACT PLATING
  - 8: FULL GOLD FLASH
- CONNECTOR TYPE
  - P:PLUG
- No.OF CONTACTS
  - 2*1-2*40

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

DRAWING TYPE	CUSTOMER		
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C-DS1031-06-XXXXXXX		

PROJECTION		TITLE	1.27mm PITCH PIN HEADER DUAL ROW STRAIGHT
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1031-06 SERIES

CONNFLY