

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	HP 25/06/05		

NOTES:

1. SPECIFICATIONS

- Current Rating: 1A
- Insulation Resistance: 500MΩ Min
- Dielectric Withstanding: 300V AC
- Contact Resistance: 30mΩ Max
- Operating Temperature: -40°C to +105°C

2. MATERIALS

- Contact Material: Copper alloy
- Insulator: Thermoplastic(UL94 V-0).

3. PART NUMBER: DS1065-01

4. PRODUCT NUMBER CODE:

DS1065-01 - X X X X X

- MOUNTING TYPE
V:V/T TYPE
- HOUSING COLOR
B:BLACK
- CONTACT PLATING
8: FULL GOLD FLASH
- CONNECTOR TYPE
S:SOCKET
- No.OF CONTACTS
1*1-1*40

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	FEMALE HEADER PITCH 1.27mm TYPE	
X.	±0.60	X.	±5°	UNITS	mm	SINGLE ROW V/T TYPE		
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1065-01	
.XX	±0.25	.XX	±2°	<div> CONNFLY</div>				
DRAWING TYPE		CUSTOMER						
SCALE	1:1	SHEET	1 OF 1					
DRAWING NO.	C-DS1065-01-XXXXX							

