

1	2	3	4	5	A																																																																																												
<div><p>Note: 1.Material: 1.1 Front Insulator: P.B.T UL 94-V0 rated. 1.2 Back Insulator: PA66 UL 94-V0 rated. 1.3 Contact: Brass,t=0.20mm. 1.4 Shell: Cold rolled steel,t=0.40mm.</p><p>2.Specification: 2.1 Current rating: 1 A Max. 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute. 2.3 Contact resistance: 30 mΩ Max. 2.4 Insulation resistance: 1000 MΩ Min at DC 500V. 2.5 Temperature range: -55℃~+105℃</p></div>					B																																																																																												
<div><table><tr><td>A</td><td>前鉗型(不通孔)</td><td>B</td><td>后鉗型(通孔)</td></tr><tr><td colspan="2"></td><td colspan="2"></td></tr></table></div>					A	前鉗型(不通孔)	B	后鉗型(通孔)					C																																																																																				
A	前鉗型(不通孔)	B	后鉗型(通孔)																																																																																														
<table><tr><td>6</td><td>8.0 Nut</td><td>2</td><td>Brass</td><td>H4.75*8.0</td><td>Nickel Plated</td></tr><tr><td>5</td><td>3B Nut</td><td>2</td><td>Brass</td><td>H4.75*4.75</td><td>Nickel Plated</td></tr><tr><td>4</td><td>Back-shell</td><td>1</td><td>Cold Rolled Steel</td><td>T=0.40mm</td><td>Tin Plated</td></tr><tr><td>3</td><td>Front-shell</td><td>1</td><td>Cold Rolled Steel</td><td>T=0.40mm</td><td>Nickel Plated</td></tr><tr><td>2</td><td>Contact</td><td>9~37</td><td>Brass</td><td>T=0.20mm</td><td>Gold Flashed</td></tr><tr><td rowspan="2">1</td><td>Back Housing</td><td>1</td><td>PA66</td><td>UL 94-V0</td><td>Black/Blue/White</td></tr><tr><td>Front Housing</td><td>1</td><td>P.B.T</td><td>UL 94-V0</td><td>Black/Blue/White</td></tr><tr><td>No.</td><td>Part Name</td><td>Q'ty</td><td>Material</td><td>Remarks & Thickness</td><td>Finish</td></tr><tr><td>PART NO</td><td>A±0.25</td><td>B±0.25</td><td>C±0.25</td><td>D±0.25</td><td>E±0.25</td><td>G±0.25</td><td>H±0.20</td><td>I±0.20</td></tr><tr><td>CR-09P</td><td>30.80</td><td>25.00</td><td>16.92</td><td>8.30</td><td>17.70</td><td>12.60</td><td>2.77</td><td>2.84</td></tr><tr><td>CR-15P</td><td>39.20</td><td>33.32</td><td>25.25</td><td>8.30</td><td>17.70</td><td>12.60</td><td>2.77</td><td>2.84</td></tr><tr><td>CR-25P</td><td>53.05</td><td>47.04</td><td>38.96</td><td>8.30</td><td>17.70</td><td>12.60</td><td>2.77</td><td>2.84</td></tr><tr><td>CR-37P</td><td>69.40</td><td>63.50</td><td>55.42</td><td>8.30</td><td>17.70</td><td>12.60</td><td>2.77</td><td>2.84</td></tr></table>					6	8.0 Nut	2	Brass	H4.75*8.0	Nickel Plated	5	3B Nut	2	Brass	H4.75*4.75	Nickel Plated	4	Back-shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated	3	Front-shell	1	Cold Rolled Steel	T=0.40mm	Nickel Plated	2	Contact	9~37	Brass	T=0.20mm	Gold Flashed	1	Back Housing	1	PA66	UL 94-V0	Black/Blue/White	Front Housing	1	P.B.T	UL 94-V0	Black/Blue/White	No.	Part Name	Q'ty	Material	Remarks & Thickness	Finish	PART NO	A±0.25	B±0.25	C±0.25	D±0.25	E±0.25	G±0.25	H±0.20	I±0.20	CR-09P	30.80	25.00	16.92	8.30	17.70	12.60	2.77	2.84	CR-15P	39.20	33.32	25.25	8.30	17.70	12.60	2.77	2.84	CR-25P	53.05	47.04	38.96	8.30	17.70	12.60	2.77	2.84	CR-37P	69.40	63.50	55.42	8.30	17.70	12.60	2.77	2.84	D
6	8.0 Nut	2	Brass	H4.75*8.0	Nickel Plated																																																																																												
5	3B Nut	2	Brass	H4.75*4.75	Nickel Plated																																																																																												
4	Back-shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated																																																																																												
3	Front-shell	1	Cold Rolled Steel	T=0.40mm	Nickel Plated																																																																																												
2	Contact	9~37	Brass	T=0.20mm	Gold Flashed																																																																																												
1	Back Housing	1	PA66	UL 94-V0	Black/Blue/White																																																																																												
	Front Housing	1	P.B.T	UL 94-V0	Black/Blue/White																																																																																												
No.	Part Name	Q'ty	Material	Remarks & Thickness	Finish																																																																																												
PART NO	A±0.25	B±0.25	C±0.25	D±0.25	E±0.25	G±0.25	H±0.20	I±0.20																																																																																									
CR-09P	30.80	25.00	16.92	8.30	17.70	12.60	2.77	2.84																																																																																									
CR-15P	39.20	33.32	25.25	8.30	17.70	12.60	2.77	2.84																																																																																									
CR-25P	53.05	47.04	38.96	8.30	17.70	12.60	2.77	2.84																																																																																									
CR-37P	69.40	63.50	55.42	8.30	17.70	12.60	2.77	2.84																																																																																									
<table><tr><td></td><td></td><td></td><td></td><td>DRAWN:</td><td>GENERAL TOLERANCE:</td><td></td></tr><tr><td>E</td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>D</td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td colspan="4" rowspan="4"><div>勝特力材料 886-3-5753170 勝特力电子(上海) 86-21-34970699 勝特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw</div></td><td>CHECKED:</td><td>UNIT:</td><td rowspan="4">SIZE A4</td></tr><tr><td></td><td>SCALE:</td></tr><tr><td>JECSON</td><td>SHEET:</td><td>DESCRIPTION:</td></tr><tr><td>BY</td><td>PROJECTION:</td><td>PART NO: E40-xxP</td></tr></table>									DRAWN:	GENERAL TOLERANCE:		E							D							<div>勝特力材料 886-3-5753170 勝特力电子(上海) 86-21-34970699 勝特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw</div>				CHECKED:	UNIT:	SIZE A4		SCALE:	JECSON	SHEET:	DESCRIPTION:	BY	PROJECTION:	PART NO: E40-xxP																																																									
				DRAWN:	GENERAL TOLERANCE:																																																																																												
E																																																																																																	
D																																																																																																	
<div>勝特力材料 886-3-5753170 勝特力电子(上海) 86-21-34970699 勝特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw</div>				CHECKED:	UNIT:	SIZE A4																																																																																											
					SCALE:																																																																																												
				JECSON	SHEET:		DESCRIPTION:																																																																																										
				BY	PROJECTION:		PART NO: E40-xxP																																																																																										