勝 特 力 材 料 886-3-5753170
胜特力电子(上海) 86-21-34970699
胜特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw

XM–10信號連接器
XM-10 Signal Connectors



特點 Features

- 10芯信號連接器，可與SCR連接器完全相容
- 提供插頭配套（XM–10P）和R/A PCB安裝插座（XM–10R）
- 寬條狀鍍金觸點實現可靠的重複插拔,每芯可耐1A電流

- 10 Poles connector fully compatible with SCR connector
- Supply plug kit (XM–10P) and R/A PCB receptacle (XM–10R)
- Robust ribbon style gold–plated contact for reliable repetitive plugging up to 1A per pin

技術參數 Technical Data

型　號	P/N	XM-10P	XM-10R
替代品牌型號	Equivalent P/N	36210–0100PL + 36310–3200–008 (3M)　54599–1019 (MOLEX)	36110–2220PE(3M)
額定電流/電壓	Rated Current / Voltage	1A/150vac/200vdc	1A/150vac/200vdc
絕緣阻抗	Insulation Resistance	> 500MΩ @ 500VDC	> 500MΩ @ 500VDC
絕緣耐壓	Withstanding Voltage	500VRMS for 1 minute	500VRMS for 1 minute
工作溫度	Working Temperature	–40℃ to +85℃	–40℃ to +85℃
焊接溫度	Soldering Temperature	360℃ max for 10 sec. max	360℃ max for 10 sec. max
觸點材料	Contact Material	銅鍍金 Gold–plated Copper Alloy	銅鍍金 Gold–plated Copper Alloy
外殼材料	Housing Material	PC+GF　UL 94V–0	PC+GF　UL 94V–0
金屬殼體	Metal Shell Material	銅鍍鎳 Nickle–plated Copper Alloy	鋼鍍錫 Tin–plated steel
適用電纜	Applicable Wires	18~28AWG	PCB Mounting



