



Contact Current Rating: 1 Amp
Dielectric Withstanding Voltage: 500V AC
Insulation Resistance: 500MΩ/Min
Contact Resistance: 35mΩ/Max
Operation Temperature: -55°C ~ +105°C

7	HOOD	PBT+30%GF	COLOR: BLACK	
6	LATCH	ABS,SUS 304	COLOR: BLACK	
5	CLAMP	STEEL	PLATING:MATTE TIN AND NI	
4	COVER	PBT+30%GF	COLOR: BLACK	
3	HOUSING	PBT+30%GF	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 3u" SOLDER AREA: G/F UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

			QUALITY SYMBOLS	Tolerance	NAME:	3M同等品 SCS1 20P MALE SOLDER ASSEMBLY TYPE弹片式端子全金 (客户用图)				PART NO.	B01-02031132-01	
			□: ☒:	x. ±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
	2009/06/04新版发行	King Zhou	CRITICAL MAJOR	.x ±0.50	SCALE:	N:1	DATE:	2009/06/04	DAW NHU	KING ZHOU		B01-014
			▽: ▽:	.xx ±0.30								
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C								