







REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	RELEASED PER ECO-20-003383	09MAR2020	BKW	DS
	A1	REVISED PER ECR-20-100211	08AUG2020	JP	VS
	B	REVISED PER ECR-20-100662	09DEC2020	PC	DS
	C	REVISED PER ECR-22-142839	28JUL2022	PJ	VS

勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
<http://www.100y.com.tw>



- ⚠ MATERIAL: PBT, GLASS FILLED
2. FLAMMABILITY RATING: UL94 V-0
3. APPLICABLE CONTACT P/N:
2329910-*/2329907-*/2329906-*/2329908-*/2329909-*/2329911-*/
2337140-*/2337139-*
4. MATING CONNECTOR P/N
PLUG HSG: *-2336229-*/*-2337912-
TPA: 2337218-6
PERIMETER SEAL: 2325347-3 (2 PER CAP)
GANG SEAL: 2325349-3 (2 PER CAP)
5. RECOMMENDED PANEL THICKNESS: 0.80-2.00
6. PANEL MUST BE PUNCHED SO THAT THE HOUSING ENTERS THE PANEL
IN THE SAME DIRECTION AS THE PUNCH
- ⚠ PRELIMINARY PART - NOT RELEASED FOR PRODUCTION




2x3 POSITION




RECOMMENDED PANEL CUT-OUT
(ALL DIMENSIONS ±0.15)



KEY A



KEY B



KEY C

BROWN	KEY C	2*3	⚠ 3-2337219-6
LIGHT GRAY	KEY B	2*3	⚠ 2-2337219-6
NATURAL	KEY A	2*3	1-2337219-6
COLOR	KEYING	POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B. WEAVER 20JUN2018	TE Connectivity	
DIMENSIONS:		CHK S. FERNANDES 20JUN2018		
mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD C. YI 20JUN2018	NAME CAP HOUSING, POWER VERSA-LOCK	
	0 PLC	±	SIZE	
	1 PLC	±0.35	CAGE CODE	
	2 PLC	±0.25	DRAWING NO	
	3 PLC	±	RESTRICTED TO	
MATERIAL	4 PLC	±	A100779C=2337219	
	ANGLES	±	SCALE 4:1	
	FINISH	-	SHEET 1 OF 1	
		-	REV C	
CUSTOMER DRAWING				