
A3

N° C 130008



1 WIRE INS. DIA 2.67-3.56mm

勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
胜特力电子(上海) 86-21-34970699
胜特力电子(深圳) 86-755-83298787
http://www.100y.com.tw

REFERENCE: 130008-0

REFERENCE SUR BANDE: 2-130008-1

TOL = ±0.20

REV	MODIFICATIONS	DES	DATE
H	ECO-20-007109	DR	17NOV 2020
G1	REVISED PER ECO-11-004917	RK	21MAR11

NUMERO	DESCRIPTION	OBSERVATION	REP.
	DESSIN CLIENT UNIQUEMENT POUR REFERENCES		

DESSINE LE 02/02/90 PAR G. ROBERT

VERIFIE LE - PAR -

MATIERE CUIVRE

FINITION ETAIN

OTHERS: FIL 22/16 ISOLANT 2.6/3.5

PLAN FAIT EN CAO

TOLERANCES SAUF INDICATION ±5°

ECHELLE -

TE Connectivity

CLASSE

TYPE


N° C130008 REV H

COSSE PIDG

PLAN CLIENT

DIST -







PIDG TERMINALS & SPLICES

Quick Reference Guide

FEATURES AND BENEFITS

- Made of high conductivity copper; tin-plated for optimal corrosion protection
- Copper sleeve for vibration resistance and improved wire insulation support
- Body has inner serrations for maximum electrical contact and tensile strength
- Insulation sleeves are colour-coded by wire size to the corresponding TE Connectivity (TE) tooling for easy identification and termination
- Readily available at distributors in small packages or bulk quantities
- Most PIDG terminals and splices are UL/CSA listed and Mil-Spec approved
- Operating temperature 105°C; operating voltage 300V

300V

Operating Voltage

105°

Max Operating Temperature (in C)

MIL

MIL-SPEC Approval


PRODUCT APPLICATIONS

- Instruments/Control
- Lighting
- Power Supplies
- Panel Boxes
- Transportation
- Lifting equipment
- Motors
- Aerospace
- Appliances



WHAT'S INSIDE

TE Connectivity's PIDG terminals are designed for uniform reliability in the harshest circuit environments, especially where high vibration and wire movement are factors. They consist of a nylon or PVC insulated body, plus a metal sleeve that crimps to the wire insulation for added support. The wire barrel design is vibration resistant, and supports the wire to bend in any direction without damaging the wire insulation or conductor. Millions of PIDG terminals and splices are still in the field many years after installation; a testament to the rigorous testing and research that went into their design and manufacturing. Many PIDG terminals meet or exceed the requirements of SAE AS7928, Type II, Class 1 and 2.



MATERIAL


Insulation: Nylon, UL 94V-2
Terminal Body: Copper per ASTM B-152
Plating: Tin per ASTM B-545
Metallic Sleeve: Copper per ASTM B-152

Ring Tongue Terminals

Wire Size		Studsize		Standard Part Number	Width (W)		Length (L)		Color	Max. Wire Insulation Dia.		Also available in		Re-marks	Manual Hand Tools			Die Sets for Powered Tools (See Note 1 for Powered Tool Options)	
AWG	mm²	U.S.	mm		inch	mm	inch	mm		inch	mm	Tape & Reel	Small Pack		Certi-Crimp Hand Tool Most UL Apvd	Mil-Spec Certified Hand Tool	Pro-Crimper (SDE) Hand Tool	SDE Die Set (Premium) Most UL Apvd	SDE Die Set (Commercial)
26-24	0,12-0,24	**2**	M2	**54310-1**	**.203**	5,16	**.739**	18,77	Yellow	**.105**	2,67			0,6	46121				
		4	M2.5	**52189**	**.203**	5,16	**.736**	18,69	Yellow	**.105**	2,67			0,6	46121				
		6	M3.5	**53073**	**.250**	6,35	**.792**	20,12	Yellow	**.105**	2,67			0,6	46121				
		8	M4	**54311-1**	**.281**	7,14	**.814**	20,68	Yellow	**.105**	2,67			0,6	46121				
		10		**54312-1**	**.312**	7,92	**.868**	22,05	Yellow	**.105**	2,67	✔		0,6	46121				
26-22	0,12-0,41	**0**		**321013**	**.140**	3,56	**.525**	13,34	Yellow	**.082**	2,08				46121				
		2	M2	**323912**	**.140**	3,56	**.525**	13,34	Yellow	**.082**	2,08	✔	✔		46121				
		2	M2	**329951**	**.140**	3,56	**.615**	15,62	Yellow	**.082**	2,08				46121				
		4	M2.5	**323914**	**.203**	5,16	**.646**	16,41	Yellow	**.082**	2,08	✔	✔	6	46121				
		6	M3.5	**326875**	**.250**	6,35	**.740**	18,80	Yellow	**.082**	2,08	✔	✔	6	46121				
		6	M3.5	**323915**	**.203**	5,16	**.646**	16,41	Yellow	**.082**	2,08	✔	✔		46121				
		8	M4	**323916**	**.250**	6,35	**.740**	18,80	Yellow	**.082**	2,08	✔	✔	6	46121				
		10		**324075**	**.250**	6,35	**.765**	19,43	Yellow	**.082**	2,08	✔	✔	6	46121				
24-20	0,16-0,65	**2**	M2	**329636**	**.106**	4,06	**.589**	14,96	White	**.100**	2,54				47907-1				
		4	M2.5	**323985**	**.281**	7,14	**.774**	19,66	White	**.100**	2,54				47907-1				
		6	M3.5	**323986**	**.281**	7,14	**.774**	19,66	White	**.100**	2,54	✔			47907-1				
		8	M4	**323989**	**.312**	7,92	**.821**	20,85	White	**.100**	2,54	✔			47907-1				
		10		**323990**	**.312**	7,92	**.821**	20,85	White	**.100**	2,54	✔			47907-1				
22-16	0,26-1,65	**2**	M2	**328657**	**.218**	5,54	**.672**	17,07	Red	**.125**	3,18	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		4	M2.5	**320553**	**.218**	5,54	**.672**	17,07	Red	**.125**	3,18	✔	✔	6	47386	59250	58433-3	2063030-1	58423-1
		4	M2.5	**31880**	**.218**	5,54	**.672**	17,07	Red	**.140**	3,65	✔	✔	6	47386	59250	58433-3	2063030-1	58423-1
		4	M2.5	**323758**	**.250**	6,35	**.844**	21,44	Red	**.125**	3,18	✔			47386	59250	58433-3	2063030-1	58423-1
		4	M2.5	**330648**	**.250**	6,35	**.844**	21,44	Red	**.140**	3,56	✔			47386	59250	58433-3	2063030-1	58423-1
		6	M3.5	**51863**	**.250**	6,35	**.782**	19,86	Red	**.125**	3,18	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		6	M3.5	**36151**	**.281**	7,14	**.797**	20,24	Red	**.125**	3,18	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		6	M3.5	**36152**	**.281**	7,14	**.797**	20,24	Red	**.140**	3,56	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		6	M3.5	**36149**	**.218**	5,54	**.672**	17,07	Red	**.125**	3,18	✔	✔	6	47386	59250	58433-3	2063030-1	58423-1
		6	M3.5	**36150**	**.218**	5,54	**.672**	17,07	Red	**.140**	3,56	✔	✔	6	47386	59250	58433-3	2063030-1	58423-1
		8	M4	**320554**	**.281**	7,14	**.797**	20,24	Red	**.125**	3,18	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		8	M4	**31886**	**.281**	7,14	**.797**	20,24	Red	**.140**	3,56	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		8	M4	**320551**	**.312**	7,92	**.844**	21,44	Red	**.125**	3,18	✔		6	47386	59250	58433-3	2063030-1	58423-1
		8	M4	**31890**	**.312**	7,92	**.844**	21,44	Red	**.140**	3,56	✔	✔	6	47386	59250	58433-3	2063030-1	58423-1
		10		**320552**	**.281**	7,14	**.797**	20,24	Red	**.125**	3,18	✔			47386	59250	58433-3	2063030-1	58423-1
		10		**31887**	**.281**	7,14	**.797**	20,24	Red	**.140**	3,56	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		10		**36153**	**.312**	7,92	**.844**	21,44	Red	**.125**	3,18	✔	✔	6	47386	59250	58433-3	2063030-1	58423-1
		10		**36154**	**.312**	7,92	**.844**	21,44	Red	**.140**	3,56	✔	✔	6	47386	59250	58433-3	2063030-1	58423-1
			M5	**130008**	**.312**	7,92	**.850**	21,60	Red	**.140**	3,56	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		1/4	M6	**320571**	**.469**	11,91	**1.078**	27,38	Red	**.125**	3,18	✔	✔	6	47386	59250	58433-3	2063030-1	58423-1
		1/4	M6	**31894**	**.469**	11,91	**1.078**	27,38	Red	**.140**	3,56	✔	✔	6	47386	59250	58433-3	2063030-1	58423-1
			M6	**130046**	**.469**	11,91	**1.083**	27,50	Red	**.140**	3,56		✔		47386	59250	58433-3	2063030-1	58423-1
		5/16	M8	**320572**	**.469**	11,91	**1.078**	27,38	Red	**.125**	3,18	✔		6	47386	59250	58433-3	2063030-1	58423-1
		5/16	M8	**31895**	**.469**	11,91	**1.078**	27,38	Red	**.140**	3,56	✔	✔	6	47386	59250	58433-3	2063030-1	58423-1
		3/8		**320573**	**.531**	13,49	**1.218**	30,94	Red	**.125**	3,18	✔		6	47386	59250	58433-3	2063030-1	58423-1
		3/8		**31897**	**.531**	13,49	**1.218**	30,94	Red	**.140**	3,56	✔	✔	6	47380	59250	58433-3	2063030-1	58423-1
		1/2	M12	**328975**	**.713**	18,11	**1.293**	32,84	Red	**.125**	3,18		✔	6	47380	59250	58433-3	2063030-1	58423-1


Ring Tongue Terminals (continued)

Wire Size		Studsize		Standard Part Number	Width (W)		Length (L)		Color	Max. Wire Insulation Dia.		Also available in		Re-marks	Manual Hand Tools			Die Sets for Powered Tools (See Note 1 for Powered Tool Options)	
AWG	mm²	U.S.	mm		inch	mm	inch	mm		inch	mm	Tape & Reel	Small Pack		Certi-Crimp Hand Tool Most UL Apvd	Mil-Spec Certified Hand Tool	Pro-Crimper (SDE) Hand Tool	SDE Die Set (Premium) Most UL Apvd	SDE Die Set (Commercial)
16-14	1,04-2,62	**2**	M2	**324993**	**.180**	4,57	**.668**	16,97	Blue	**.170**	4,32	✔	✔		47387	59250	58433-3	2063030-1	58423-1
		4	M2.5	**324159**	**.250**	6,35	**.703**	17,86	Blue	**.150**	3,81	✔			47387	59250	58433-3	2063030-1	58423-1
		4	M2.5	**328996**	**.250**	6,35	**.703**	17,86	Blue	**.170**	4,32				47387	59250	58433-3	2063030-1	58423-1
		6	M3.5	**320561**	**.250**	6,35	**.703**	17,86	Blue	**.150**	3,81	✔			47387	59250	58433-3	2063030-1	58423-1
		6	M3.5	**320619**	**.250**	6,35	**.703**	17,86	Blue	**.170**	4,32				47387	59250	58433-3	2063030-1	58423-1
		6	M3.5	**326882**	**.312**	7,92	**.813**	20,65	Blue	**.170**	4,32	✔	✔		47387	59250	58433-3	2063030-1	58423-1
		6	M3.5	**51864**	**.312**	7,92	**.844**	21,44	Blue	**.150**	3,81	✔	✔	6	47387	59250	58433-3	2063030-1	58423-1
		8	M4	**51864-1**	**.312**	7,92	**.844**	21,44	Blue	**.150**	3,81	✔	✔	6	47387	59250	58433-3	2063030-1	58423-1
		8	M4	**320560**	**.343**	8,71	**.859**	21,82	Blue	**.150**	3,81	✔	✔		47387	59250	58433-3	2063030-1	58423-1
		8	M4	**320565**	**.343**	8,71	**.859**	21,82	Blue	**.170**	4,32	✔	✔		47387	59250	58433-3	2063030-1	58423-1
		10		**320574**	**.343**	8,71	**.859**	21,82	Blue	**.150**	3,81	✔	✔		47387	59250	58433-3	2063030-1	58423-1
		10		**36160**	**.343**	8,71	**.859**	21,82	Blue	**.170**	4,32	✔	✔		47387	59250	58433-3	2063030-1	58423-1
			M5	**130090**	**.343**	8,71	**.864**	21,94	Blue	**.150**	3,80	✔			47387	59250	58433-3	2063030-1	58423-1
			M5	**130094**	**.343**	8,71	**.864**	21,94	Blue	**.170**	4,30	✔	✔		47387	59250	58433-3	2063030-1	58423-1
		1/4	M6	**320563**	**.469**	11,91	**1.078**	27,38	Blue	**.150**	3,81	✔	✔	6	47387	59250	58433-3	2063030-1	58423-1
		1/4	M6	**321045**	**.469**	11,91	**1.078**	27,38	Blue	**.170**	4,32	✔	✔		47387	59250	58433-3	2063030-1	58423-1
		5/16	M8	**320575**	**.469**	11,91	**1.078**	27,38	Blue	**.150**	3,81	✔		6	47387	59250	58433-3	2063030-1	58423-1
		5/16	M8	**328998**	**.469**	11,91	**1.078**	27,38	Blue	**.170**	4,32	✔	✔		47387	59250	58433-3	2063030-1	58423-1
		3/8		**320564**	**.531**	13,49	**1.218**	30,94	Blue	**.150**	3,81	✔	✔	6	47387	59250	58433-3	2063030-1	58423-1
		3/8		**328999**	**.531**	13,49	**1.218**	30,94	Blue	**.170**	4,32	✔	✔		47387	59250	58433-3	2063030-1	58423-1
		1/2	M12	**328976**	**.713**	18,11	**1.293**	32,84	Blue	**.150**	3,81			6	47387	59250	58433-3	2063030-1	58423-1
		1/2	M12	**328849**	**.713**	18,11	**1.293**	32,84	Blue	**.170**	4,32				47387	59250	58433-3	2063030-1	58423-1
12-10	2,62-6,64	**4**	M2.5	**35148**	**.281**	7,14	**.953**	24,21	Yellow	**.250**	6,35	✔	✔			59239-4	58433-3	2063030-1	58423-1
		6	M3.5	**320634**	**.281**	7,14	**.953**	24,21	Yellow	**.230**	5,84	✔				59239-4	58433-3	2063030-1	58423-1
		6	M3.5	**35149**	**.281**	7,14	**.953**	24,21	Yellow	**.250**	6,35	✔	✔			59239-4	58433-3	2063030-1	58423-1
		6	M3.5	**320567**	**.375**	9,53	**1.083**	27,51	Yellow	**.230**	5,84	✔		6		59239-4	58433-3	2063030-1	58423-1
		6	M3.5	**35107**	**.375**	9,53	**1.083**	27,51	Yellow	**.250**	6,35	✔	✔	6		59239-4	58433-3	2063030-1	58423-1
		8	M4	**35787**	**.312**	7,92	**1.031**	26,19	Yellow	**.230**	5,84	✔				59239-4	58433-3	2063030-1	58423-1
		8	M4	**324915**	**.312**	7,92	**1.052**	26,72	Yellow	**.230**	5,84					59239-4	58433-3	2063030-1	58423-1
		8	M4	**320568**	**.375**	9,53	**1.083**	27,51	Yellow	**.230**	5,84	✔		6		59239-4	58433-3	2063030-1	58423-1
		8	M4	**35108**	**.375**	9,53	**1.083**	27,51	Yellow	**.250**	6,35	✔	✔	6		59239-4	58433-3	2063030-1	58423-1
		10		**324918**	**.312**	7,92	**1.052**	26,72	Yellow	**.230**	5,84	✔	✔			59239-4	58433-3	2063030-1	58423-1
		10		**32883**	**.343**	8,71	**1.046**	26,57	Yellow	**.230**	5,84	✔				59239-4	58433-3	2063030-1	58423-1
			M5	**130171**	**.375**	9,53	**1.090**	27,68	Yellow	**.250**	6,35	✔				59239-4	58433-3	2063030-1	58423-1
		10		**36161**	**.375**	9,53	**1.083**	27,51	Yellow	**.230**	5,84	✔	✔	6		59239-4	58433-3	2063030-1	58423-1
		10		**35109**	**.375**	9,53	**1.083**	27,51	Yellow	**.250**	6,35	✔	✔	6		59239-4	58433-3	2063030-1	58423-1
		1/4	M6	**320569**	**.531**	13,49	**1.322**	33,58	Yellow	**.230**	5,84			6		59239-4	58433-3	2063030-1	58423-1
		1/4	M6	**35110**	**.531**	13,49	**1.322**	33,58	Yellow	**.250**	6,35	✔	✔	6		59239-4	58433-3	2063030-1	58423-1
		5/16	M8	**320576**	**.531**	13,49	**1.322**	33,58	Yellow	**.230**	5,84	✔				59239-4	58433-3	2063030-1	58423-1
		5/16	M8	**35111**	**.531**	13,49	**1.322**	33,58	Yellow	**.250**	6,35	✔	✔	6		59239-4	58433-3	2063030-1	58423-1
		5/16	M8	**160298**	**.500**	12,70	**1.188**	30,18	Yellow	**.250**	6,35	✔				59239-4	58433-3	2063030-1	58423-1
		3/8		**320577**	**.593**	15,06	**1.414**	35,92	Yellow	**.230**	5,84	✔		6		59239-4	58433-3	2063030-1	58423-1
		3/8		**35112**	**.593**	15,06	**1.414**	35,92	Yellow	**.250**	6,35		✔	6		59239-4	58433-3	2063030-1	58423-1
		1/2	M12	**323784**	**.750**	19,05	**1.594**	40,49	Yellow	**.230**	5,84					59239-4	58433-3	2063030-1	58423-1
		1/2	M12	**35151**	**.750**	19,05	**1.594**	40,49	Yellow	**.250**	6,35		✔			59239-4	58433-3	2063030-1	58423-1
		3/4		**324615**	**1.25**	31,75	**2.219**	56,36	Yellow	**.230**	5,84					59239-4	58433-3	2063030-1	58423-1



Spades: Standard Spade

Wire Size		Studsize		Standard Part Number	Width (W)		Length (L)		Color	Max. Wire Insulation Dia.		Also available in		Re-marks	Manual Hand Tools			Die Sets for Powered Tools (See Note 1 for Powered Tool Options)	
AWG	mm²	U.S.	mm		inch	mm	inch	mm		inch	mm	Tape & Reel	Small Pack		Certi-Crimp Hand Tool Most UL Apvd	Mil-Spec Certified Hand Tool	Pro-Crimper (SDE) Hand Tool	SDE Die Set (Premium) Most UL Apvd	SDE Die Set (Commercial)
26-22	0,10-0,41	**0**		**322001**	**.125**	3,18	**.476**	12,09		**.082**	2,08				46121				
		4	M2.5	**321035**	**.203**	5,16	**.627**	15,93		**.082**	2,08				46121				
22-16	0,26-1,65	**2**	M2	**328394**	**.182**	4,62	**.727**	18,47		**.140**	3,56		✔		47386	59250	58433-3	2063030-1	58423-1
		4	M2.5	**327717**	**.218**	5,54	**.674**	17,12		**.125**	3,18	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		5	M3	**34541**	**.297**	7,54	**.846**	21,49		**.140**	3,56	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		6	M3.5	**34080**	**.297**	7,54	**.753**	19,13		**.125**	3,18	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		6	M3.5	**326861**	**.297**	7,54	**.753**	19,13		**.140**	3,56	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		8	M4	**32050**	**.375**	9,53	**.908**	23,06		**.125**	3,18				47386	59250	58433-3	2063030-1	58423-1
		8	M4	**32053**	**.375**	9,53	**.908**	23,06		**.140**	3,56	✔	✔		47386	59250	58433-3	2063030-1	58423-1
		10		**32051**	**.375**	9,53	**.908**	23,06		**.125**	3,18	✔			47386	59250	58433-3	2063030-1	58423-1
		10		**32054**	**.375**	9,53	**.908**	23,06		**.140**	3,56	✔	✔		47386	59250	58433-3	2063030-1	58423-1
16-14	1,04-2,62	**4**	M2.5	**130527**	**.250**	6,35	**.813**	20,65		**.170**	4,32				47387	59250	58433-3	2063030-1	58423-1
		6	M3.5	**32058**	**.375**	9,35	**.908**	23,06		**.170**	4,32				47387	59250	58433-3	2063030-1	58423-1
		6	M3.5	**35559**	**.297**	7,54	**.753**	19,13		**.170**	4,32	✔	✔		47387	59250	58433-3	2063030-1	58423-1
		8	M4	**32056**	**.385**	9,78	**.908**	23,06		**.150**	3,81	✔	✔		47387	59250	58433-3	2063030-1	58423-1
		8	M4	**32059**	**.385**	9,78	**.908**	23,06		**.170**	4,32		✔		47387	59250	58433-3	2063030-1	58423-1
		10		**32057**	**.385**	9,78	**.908**	23,06		**.150**	3,81				47387	59250	58433-3	2063030-1	58423-1
		10		**32060**	**.385**	9,78	**.908**	23,06		**.170**	4,32		✔		47387	59250	58433-3	2063030-1	58423-1
		12	M6	**130537**	**.475**	12,07	**1.103**	28,01		**.170**	4,32		✔		47387	59250	58433-3	2063030-1	58423-1
12-10	2,62-6,64	**6**	M3.5	**322985**	**.290**	7,37	**.954**	24,23		**.230**	5,84	✔			47387	59250	58433-3	2063030-1	58423-1
		6	M3.5	**326859**	**.312**	7,92	**1.095**	27,81		**.230**	5,84	✔				59239-4	58433-3	2063030-1	58423-1
		8	M4	**32588**	**.406**	10,31	**1.095**	27,81		**.230**	5,84	✔	✔			59239-4	58433-3	2063030-1	58423-1
		8	M4	**35152**	**.406**	10,31	**1.095**	27,81		**.250**	6,35	✔	✔			59239-4	58433-3	2063030-1	58423-1
		10		**32589**	**.406**	10,31	**1.095**	27,81		**.230**	5,84	✔	✔			59239-4	58433-3	2063030-1	58423-1
		12	M6	**130625**	**0.531**	13,50	**1.299**	33,00		**0.252**	6,40		✔			59239-4	58433-3	2063030-1	58423-1



Long Spring Spade

Wire Size		Studsize		Standard Part Number	Width (W)		Length (L)		Color	Max. Wire Insulation Dia.		Also available in		Re-marks	Manual Hand Tools			Die Sets for Powered Tools (See Note 1 for Powered Tool Options)	
AWG	mm²	U.S.	mm		inch	mm	inch	mm		inch	mm	Tape & Reel	Small Pack		Certi-Crimp Hand Tool Most UL Apvd	Mil-Spec Certified Hand Tool	Pro-Crimper (SDE) Hand Tool	SDE Die Set (Premium) Most UL Apvd	SDE Die Set (Commercial)
22-16	0,26-1,65	**6**	M3.5	**52409**	**.250**	6,35	**.276**	7,01		**.125**	3,18	✔	✔	1	47386	59250	58433-3	2063030-1	58423-1
		8	M4	**52410**	**.281**	7,14	**.290**	7,37		**.125**	3,18	✔	✔	1	47386	59250	58433-3	2063030-1	58423-1
		10		**52411**	**.343**	8,71	**.303**	7,70		**.125**	3,18	✔	✔	1	47386	59250	58433-3	2063030-1	58423-1
16-14	1,04-2,62	**6**	M3.5	**52420-1**	**.250**	6,35	**.933**	23,70		**.170**	4,32	✔	✔	1	47387	59250	58433-3	2063030-1	58423-1
		8	M4	**52421-1**	**.281**	7,14	**.979**	24,87		**.170**	4,32	✔	✔	1	47387	59250	58433-3	2063030-1	58423-1
		10		**52422-1**	**.343**	8,71	**1.005**	25,53		**.170**	4,32	✔		1	47387	59250	58433-3	2063030-1	58423-1
12-10	2,62-6,64	**8**	M4	**52431-1**	**.375**	9,53	**1.174**	29,82		**.250**	6,35	✔		1		59239-4	58433-3	2063030-1	58423-1
		10		**52432-1**	**.375**	9,53	**1.219**	30,96		**.250**	6,35	✔		1		59239-4	58433-3	2063030-1	58423-1



Short Spring Spade

Wire Size		Studsize		Standard Part Number	Width (W)		Length (L)		Color	Max. Wire Insulation Dia.		Also available in		Re-marks	Manual Hand Tools			Die Sets for Powered Tools (See Note 1 for Powered Tool Options)	
AWG	mm²	U.S.	mm		inch	mm	inch	mm		inch	mm	Tape & Reel	Small Pack		Certi-Crimp Hand Tool Most UL Apvd	Mil-Spec Certified Hand Tool	Pro-Crimper (SDE) Hand Tool	SDE Die Set (Premium) Most UL Apvd	SDE Die Set (Commercial)
26-22	0,12-0,40	**6**	M3.5	**52924**	**.250**	6,35	**.679**	17,25	●	**.082**	2,08	✔	✔	1	46121				
22-16	0,26-1,65	**4**	M2.5	**52927**	**.203**	5,16	**.799**	20,29	●	**.125**	3,18	✔	✔	1	47386	59250	58433-3	2063030-1	58423-1
		5	M3	**52928**	**.250**	6,35	**.799**	20,29	●	**.125**	3,18	✔	✔	1	47386	59250	58433-3	2063030-1	58423-1
		6	M3.5	**52929**	**.250**	6,35	**.799**	20,29	●	**.125**	3,18	✔	✔	1	47386	59250	58433-3	2063030-1	58423-1
		8	M4	**52930**	**.375**	9,53	**.860**	21,84	●	**.125**	3,18	✔	✔	1	47386	59250	58433-3	2063030-1	58423-1
		10		**52931**	**.406**	10,31	**.908**	23,06	●	**.125**	3,18	✔	✔	1	47386	59250	58433-3	2063030-1	58423-1
		12	M6	**52933**	**.625**	18,88	**1.033**	26,24	●	**.125**	3,18		✔	1	47387	59250	58433-3	2063030-1	58423-1
16-14	1,04-2,62	**5**	M3	**52934**	**.250**	6,35	**.799**	20,29	●	**.170**	4,32	✔	✔	1	47387	59250	58433-3	2063030-1	58423-1
		6	M3.5	**52935**	**.250**	6,35	**.799**	20,29	●	**.170**	4,32	✔	✔	1	47387	59250	58433-3	2063030-1	58423-1
		8	M4	**52936**	**.375**	9,53	**.860**	21,84	●	**.170**	4,32	✔	✔	1	47387	59250	58433-3	2063030-1	58423-1
		10		**52937**	**.406**	10,31	**.908**	23,06	●	**.170**	4,32	✔	✔	1	47387	59250	58433-3	2063030-1	58423-1
		12	M6	**52939**	**.625**	15,88	**1.033**	26,24	●	**.170**	4,32			1		59239-4	58433-3	2063030-1	58423-1
12-10	2,62-6,64	**5**	M3	**52940**	**.250**	6.35	**.959**	24,36	●	**.250**	6,35	✔	✔	1		59239-4	58433-3	2063030-1	58423-1
		6	M3.5	**52941**	**.250**	6,35	**.959**	24,36	●	**.250**	6,35	✔	✔	1		59239-4	58433-3	2063030-1	58423-1
		8	M4	**52942**	**.375**	9,53	**1.052**	26,72	●	**.250**	6,35	✔	✔	1		59239-4	58433-3	2063030-1	58423-1
		10		**52943**	**.406**	10,31	**1.100**	27,94	●	**.250**	6,35	✔	✔	1		59239-4	58433-3	2063030-1	58423-1
		12	M6	**52945**	**.625**	15,88	**1.225**	31,12	●	**.250**	6,35		✔	1		59239-4	58433-3	2063030-1	58423-1




Butt Splices

Wire Size		Tab Thickness		Standard Part Number	Width (W)		Length (L)		Color	Max. Wire Insulation Dia.		Also available in		Re-marks	Manual Hand Tools			Die Sets for Powered Tools (See Note 1 for Powered Tool Options)	
AWG	mm²	U.S.	mm		inch	mm	inch	mm		inch	mm	Tape & Reel	Small Pack		Certi-Crimp Hand Tool Most UL Apvd	Mil-Spec Certified Hand Tool	Pro-Crimper (SDE) Hand Tool	SDE Die Set (Premium) Most UL Apvd	SDE Die Set (Commercial)
26-24	0,12-0,24	**n.a.**		**323994**	**n.a.**		**.890**	22,61	●	**.082**	2,08	✔		6	46121				
26-22	0,12-0,41	**n.a.**		**2-323994-2**	**n.a.**		**.890**	22,61	●	**.082**	2,08		✔		46121				
24-20	0,16-0,65	**n.a.**		**323975**	**n.a.**		**1.035**	26,29	○	**.100**	2,54	✔		6	47907-1				
22-16	0,26-1,65	**n.a.**		**320559**	**n.a.**		**1.265**	32,13	●	**.125**	3,18	✔	✔	6	47386	59250	58433-3	2063030-1	58423-1
16-14	1,04-2,62	**n.a.**		**320562**	**n.a.**		**1.265**	32,13	●	**.150**	3,81	✔	✔	6	47387	59250	58433-3	2063030-1	58423-1
12-10	2,62-6,64	**n.a.**		**320570**	**n.a.**		**1.656**	42,06	●	**.220**	5,59	✔	✔	6		59239-4	58433-3	2063030-1	58423-1


Stepdown Butt Splice

16-14 to 22-18	1,04-2,62 to 0,26-0,96	**n.a.**		**327583**	**n.a.**		**1.265**	32,13	●	**.150/ .115**	3,81/ 2,92		✔	5	47387	59250	58433-3	2063030-1	58423-1
12-10 to 22-18	2,62-6,64 to 0,26-0,96	**n.a.**		**327639**	**n.a.**		**1.656**	42,06	●	**.220/ .140**	5,59/ 3,56			5		59239-4	58433-3	2063030-1	58423-1
12-10 to 16-14	2,62-6,64 to 1,04-2,62	**n.a.**		**327638**	**n.a.**		**1.656**	42,06	●	**.220/ .170**	5,59/ 4,32			5		59239-4	58433-3	2063030-1	58423-1



Knife Disconnects

Wire Size		Tab Thickness		Standard Part Number	Width (W)		Length (L)		Color	Max. Wire Insulation Dia.		Also available in		Re-marks	Manual Hand Tools			Die Sets for Powered Tools (See Note 1 for Powered Tool Options)	
AWG	mm²	U.S.	mm		inch	mm	inch	mm		inch	mm	Tape & Reel	Small Pack		Certi-Crimp Hand Tool Most UL Apvd	Mil-Spec Certified Hand Tool	Pro-Crimper (SDE) Hand Tool	SDE Die Set (Premium) Most UL Apvd	SDE Die Set (Commercial)
22-16	0,26-1,65	**n.a.**		**320555**	**.203**	5,16	**.878**	22,3	🔴	**.125**	3,18		✔		47386	59250	58433-3	2063030-1	58423-1
		n.a.		**32446**	**.203**	5,16	**.878**	22,3	🔴	**.140**	3,56	✔	✔		47386	59250	58433-3	2063030-1	58423-1
16-14	1,04-2,62	**n.a.**		**32448**	**.203**	5,16	**.878**	22,3	🔵	**.170**	4,32		✔		47387	59250	58433-3	2063030-1	58423-1
12-10	2,62-6,64	**n.a.**		**35762**	**.281**	7,14	**1.260**	32	🟡	**.250**	6,35		✔			59239-4	58433-3	2063030-1	58423-1




Wire Pins (formed)

26-22	0,12-0,41	**n.a**		**165514-1**	**.045**	1,14	**.716**	18,20	🟡	**.83**	2,11		✔		47386		58433-3	2063030-1	58423-1
22-16	0,26-1,65	**n.a.**		**165142**	**.071**	1,80	**.795**	20,20	🔴	**.142**	3,60		✔		47386	59250	58433-3	2063030-1	58423-1
				165168	**.071**	1,80	**.913**	23,20	🔴	**.142**	3,60		✔		47386	59250	58433-3	2063030-1	58423-1
16-14	1,04-2,62	**n.a.**		**165046**	**.071**	1,80	**.800**	20,30	🔵	**.170**	4,30		✔		47387	59250	58433-3	2063030-1	58423-1
				165172	**.071**	1,80	**.929**	23,60	🔵	**.170**	4,30		✔		47387	59250	58433-3	2063030-1	58423-1
12-10	2,62-6,64	**n.a.**		**165049**	**.102**	2,60	**1.146**	29,10	🟡	**.248**	6,30		✔			59239-4	58433-3	2063030-1	58423-1
				160404-2	**.138**	3,50	**1.319**	33,50	🟡	**.248**	6,30		✔	3		59239-4	58433-3	2063030-1	58423-1



Wire Pins (flat)

22-16	0,26-1,65	**n.a.**		**131331**	**.116**	2,95	**.905**	23,00	🔴	**.142**	3,60		✔	2	47386	59250	58433-3	2063030-1	58423-1
16-14	1,04-2,62	**n.a.**		**131330**	**.115**	2,92	**.891**	22,63	🔵	**.170**	4,30		✔	2	47387	59250	58433-3	2063030-1	58423-1
12-10	2,62-6,64	**n.a.**		**131332**	**1.614**	4,10	**1.150**	29,20	🟡	**.252**	6,40					59239-4	58433-3	2063030-1	58423-1



FASTON Receptacle (.250/6.35)

Wire Size		Tab Thickness		Standard Part Number	Width (W)		Length (L)		Color	Max. Wire Insulation Dia.		Also available in		Re-marks	Manual Hand Tools			Die Sets for Powered Tools (See Note 1 for Powered Tool Options)	
AWG	mm²	U.S.	mm		inch	mm	inch	mm		inch	mm	Tape & Reel	Small Pack		Certi-Crimp Hand Tool Most UL Apvd	Mil-Spec Certified Hand Tool	Pro-Crimper (SDE) Hand Tool	SDE Die Set (Premium) Most UL Apvd	SDE Die Set (Commercial)
22-18	0,26-0,96	**.032**	0,81	**640903-1**	**.300**	7,62	**.900**	22,86		**.140**	3,56	✔	✔				58433-3	2063030-1	58423-1
22-16	0,30-1,50	**.032**	0,81	**9-160583-2**	**.300**	7,62	**.874**	22,20		**.140**	3,56		✔	3			58433-3	2063030-1	58423-1
16-14	1,04-2,62	**.032**	0,81	**640905-1**	**.300**	7,62	**.900**	22,86		**.170**	4,32	✔	✔				58433-3	2063030-1	58423-1
		.032	0,81	**9-160313-2**	**.300**	7,62	**.913**	23,20		**.170**	4,32	✔	✔	3			58433-3	2063030-1	58423-1
12-10	2,62-6,64	**.032**	0,81	**640907-1**	**.300**	7,62	**1.012**	25,70		**.250**	6,35	✔	✔				58433-3	2063030-1	58423-1
11-10	4,00-6,00	**.031**	0,80	**160314-2**	**.300**	7,62	**1.015**	26,00		**.250**	6,35		✔	3					

FASTON Flag Receptacle (.250/6.35)

22-18	0,30-1,00	**.032**	0,81	**156667-1**	**.610**	15,49	**.760**	19,30		**.140**	3,56		✔	3,4			58433-3	2063030-1	58423-1
17-15	1,20-2,00	**.032**	0,81	**156666-1**	**.610**	15,49	**.760**	19,30		**.170**	4,32		✔	3			58433-3	2063030-1	58423-1

FASTON Receptacle (.205/5.00)


22-18	0,26-0,96	**.020**	0,51	**640909-1**	**.250**	6,35	**.800**	20,32		**.140**	3,56	✔	✔				58433-3	2063030-1	58423-1
		.032	0,81	**640911-1**	**.250**	6,35	**.800**	20,32		**.140**	3,56	✔	✔				58433-3	2063030-1	58423-1
16-14	1,04-2,62	**.020**	0,51	**640913-1**	**.250**	6,35	**.800**	20,32		**.170**	4,32	✔	✔				58433-3	2063030-1	58423-1
		.032	0,81	**640915-1**	**.250**	6,35	**.800**	20,32		**.170**	4,32	✔	✔				58433-3	2063030-1	58423-1

FASTON Receptacle (.187/4.80)

26-24	0.12-0.24	**.020**	0,51	**641321-1**	**.230**	5,84	**.700**	17,78		**.082**	2,08	✔	✔						
22-18	0,26-0,96	**.020**	0,51	**640917-1**	**.230**	5,84	**.800**	20,32		**.140**	3,56	✔	✔				58433-3	2063030-1	58423-1
22-15	0,30-1,50	**.020**	0,51	**9-160481-1**	**.226**	5,74	**.822**	20,88		**.140**	3,56	✔	✔	3					
		.031	0,80	**9-160483-1**	**.226**	5,74	**.822**	20,88		**.140**	3,56	✔	✔	3					
16-14	1,04-2,62	**.020**	0,51	**640919-1**	**.230**	5,84	**.800**	20,32		**.170**	4,32	✔	✔				58433-3	2063030-1	58423-1
		.020	0,50	**9-160477-2**	**.230**	5,84	**.862**	21,90		**.170**	4,30	✔	✔	3					
		.031	0,80	**9-160479-2**	**.226**	5,74	**.862**	21,90		**.170**	4,30	✔	✔	3					


FASTON Receptacle (.110/2.80)

22-18	0,26-0,96	**.020**	0,51	**61060-1**	**.148**	3,76	**.734**	18,64		**.110**	2,79	✔	✔						
		.032	0,81	**60894-1**	**.148**	3,76	**.734**	18,64		**.110**	2,79	✔	✔						
22-16	0,30-1,50	**.031**	0,80	**165566-1**	**.146**	3,70	**.780**	19,80		**.138**	3,50		✔	3					
		.020	0,50	**165565-1**	**.146**	3,70	**.780**	19,80		**.138**	3,50	✔	✔	3					
16-14	1,50-2,50	**.020**	0,51	**165616-2**	**.146**	3,70	**.780**	19,80		**.170**	4,30	✔	✔	3					
		.010	0,25	**165617-2**	**.146**	3,70	**.780**	19,80		**.170**	4,30	✔	✔	3					




FASTON (.110/2.80) Low insertion force terminal

Wire Size		Tab Thickness		Standard Part Number	Width (W)		Length (L)		Color	Max. Wire Insulation Dia.		Also available in		Re-marks	Manual Hand Tools			Die Sets for Powered Tools (See Note 1 for Powered Tool Options)	
AWG	mm²	U.S.	mm		inch	mm	inch	mm		inch	mm	Tape & Reel	Small Pack		Certi-Crimp Hand Tool Most UL Apvd	Mil-Spec Certified Hand Tool	Pro-Crimper (SDE) Hand Tool	SDE Die Set (Premium) Most UL Apvd	SDE Die Set (Commercial)
26-24	0,12-0,24	**.020**	**0,51**	**641324-1**	**.160**	4,06	**.700**	17,78	●	**.082**	2,08	✔							
22-18	0,26-0,96	**.016**	**0,41**	**640921-1**	**.160**	4,06	**.800**	20,32	●	**.140**	3,56	✔					58433-3	2063030-1	58423-1
		.020	**0,51**	**640923-1**	**.160**	4,06	**.800**	20,32	●	**.140**	3,56	✔	✔				58433-3	2063030-1	58423-1
		.032	**0,81**	**640925-1**	**.160**	4,06	**.800**	20,32	●	**.140**	3,56	✔	✔				58433-3	2063030-1	58423-1
16-14	1,04-2,62	**.020**	**0,51**	**640929-1**	**.160**	4,06	**.800**	20,32	●	**.170**	4,32	✔	✔				58433-3	2063030-1	58423-1
		.032	**0,81**	**640931-1**	**.160**	4,06	**.800**	20,32	●	**.170**	4,30	✔	✔				58433-3	2063030-1	58423-1



Tab Terminal

20-18	0,50-1,00	**.031**	**0,80**	**140896-2**	**.250**	6,35	**.925**	23,50	●	**.130**	3,30		✔	3	90035-3				
16-14	1,30-2,60	**.031**	**0,80**	**140971-2**	**.250**	6,35	**.925**	23,50	●	**.157**	4,00		✔	3	90009-8				
11-10	4,00-6,00	**.031**	**0,80**	**141085-2**	**.250**	6,35	**1.102**	28,00	●	**.224**	5,70		✔	3	90276-2				




TAB (.250 splice for receptacle)

22-10	0,26-6,00	**.032**	**0,81**	**1-321235-0**	**.409**	10,39	**2.625**	66,68	○	**n.a**									
				1-321235-1	**.409**	10,39	**2.625**	66,68	○	**n.a**									
				321235	**.409**	10,39	**2.093**	53,16	○	**n.a**									



Piggy Back Terminal

22-16	0,26-1,65	**.032**	**0,81**	**160834-2**	**.250**	6,35	**.927**	23,55	●	**.140**	3,56		✔	3	47386-4				
16-14	1,00-2,50	**.032**	**0,81**	**9-160463-2**	**.250**	6,35	**.922**	23,45	●	**.170**	4,32		✔	3	47387-7				



Receptacle Pin

SHUR-PLUG Terminals

Wire Size		Style		Standard Part Number	Width (W)		Length (L)		Color	Max. Wire Insulation Dia.		Also available in		Re-marks	Manual Hand Tools			Die Sets for Powered Tools (See Note 1 for Powered Tool Options)	
AWG	mm²				inch	mm	inch	mm		inch	mm	Tape & Reel	Small Pack		Certi-Crimp Hand Tool Most UL Apvd	Mil-Spec Certified Hand Tool	Pro-Crimper (SDE) Hand Tool	SDE Die Set (Premium) Most UL Apvd	SDE Die Set (Commercial)
22-16	0,25-1,60	**Pin**		**165590-1**	**.156**	3,96	**.799**	20,30	●	**.138**	3,50		✔						
	0,50-1,50	**Pin**		**141462-1**	**.118**	3,00	**.945**	24,00	●	**.134**	3,40		✔						
		Recpt		**141456-1**	**.118**	3,00	**.984**	25,00	●	**.130**	3,30		✔						
	0,50-1,60	**Recpt**		**165399-1**	**.156**	3,96	**.902**	22,90	●	**.114**	2,90		✔						
16-14	1,04-2,62	**Pin**		**324225**	**.156**	3,96	**.790**	20,07	●	**.170**	4,32	✔	✔		47387-7		58433-3	2063030-1	58423-1
	1,04-2,62	**Recpt**		**165429-1**	**.156**	3,96	**.972**	24,70	●	**.157**	4,00		✔						

REMARKS

0 Must be crimped with 22-18 or 22-16 PIDG (red) tooling
1 Body Springs Spade : Phosphor Bronze per ASTM B-139
2 Body : Copper also according DIN 1787 and EN 1676
3 Body : Brass according ASTM B 36
4 Sleeve : Nickel Plating per SAE AMS QQ-N-290
5 Adapter inserts can be ordered seperately for use in specific standard PIDG Butt Splices
6 Mill Specified
7 Body : Brass according MIL-C-50
For all remarks and additional information see Customer Drawing on www.te.com

NOTE 1

The die sets listed above can be used with the following powered tools:
1.75 Ton Battery Tools 2217480-1 (110V) or 2217480-2 (220V)
AT-300 Electric Crimping Machine 539630-2 (115V/230V) with SDE Adapter 1673663-2
626 Pneumatic Tool System with Pro-Crimper Adapter 679304-1
AT-SC MK II Pneumatic Safety Crimping Machine 1-528050-0 with SDE Die Holder 2-528051-8

NOTE 2

Most 22-16, 16-14, and 12-10 AWG PIDG terminals and splices can be crimped using TETRA-CRIMP Hand Crimping Tool 59824-1 (UL approved)

FREQUENTLY ASKED QUESTIONS TOOLING

Can wires be combined in PIDG terminals & splices?
Yes, they can as long total CMA (Circular Mil Area) and insulation diameter fall within specifi cation.
Are PIDG terminals MIL specified?
Yes, most of them meet or exceed MIL-T-7928, Type II, class 1 & 2.
What product should you choose if you need higher temperature?
Use TE STRATO-THERM terminals (catalog 82011).
Why can PIDG terminals just handle 300V and PLASTI-GRIP terminals 600 V?
Because the additional copper sleeve is close to the end of the sleeve.
What is the advantage of this copper sleeve?
It provides circumferential insulation support to the wire and allows the wire to bend in any direction, without fraying the wire's insulation or breaking the conductor.
Why is there no crimp height given for PIDG terminals?
It is the geometry of the TE crimping tools which ensures the perfect crimp on PIDG terminals.



1. The conical sleeve serves for easier conductor insertion.
2. The nylon insulating sleeve offers high dielectric strength. The colour coding corresponds to the wire size.
3. Grooves inside the wire sleeve ensure high tensile strength and current transfer.
4. The copper sleeve provides optimal insulation support.

TOOLING



58433-3 - Pro-Crimper
Commercial Hand Tool

http://tooling.te.com

For questions about our connectivity solutions, please go to te.com.

www.te.com/products/industrial-terminals-splices

© 2018 TE Connectivity All Rights Reserved.

PIDG, FASTON, STRATO-THERM, Certi-Crimp, TETRA-CRIMP, Pro-Crimper, TE, TE Connectivity (logo) are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

1-1773934-5 CC 09/18