Slimline PCB Relay SNR

- 1 pole 6A, 1 form C (CO), 1 form A (NO)
- Only 5mm wide
- Flat pack version available
- Sensitive coil 170mW
- Reinforced insulation (protection classII)
- Strong coil pins for DIN-rail socket
- Allows high function- / packaging density
- Cadmium-free contacts, AgNi 90/10 for AC-loads

勝 特 力 材 料 886-3-5753170
胜特力电子(上海) 86-21-34970699
胜特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw

F0140-D

Typical applications
Interface technology, PLC's, timers, centralized and decentralized heating control

Approvals

VDE REG.-Nr. 6666, UL E214024
Technical data of approved types on request

Contact Data

Contact arrangement	1 form C (CO) or 1 form A (NO)	
Rated voltage	250VAC	
Max. switching voltage	400VAC	
Rated current	6A	
Limiting making current, max 4s, df 10%	10A	
Breaking capacity max.	1500VA	
Contact material	$AgSnO_2$, AgNi 90/10	$AgSnO_2$ gold plated
Min. recommended contact load	100mA, 12V	50mW
Frequency of operation, with/without load	6/1200min^{-1}	
Operate/release time max.	12/5ms	
Bounce time max., form A/form B	3/8ms	

Contact ratings

Type	Contact	Load	Cycles
EC 61810			
V23092-*****-A301, -A801	C (CO)	6A, 250VAC, cosφ=1, 85°C	$5x10^3$
UL 508			
V23092-*****-A301, -A801	A/B	6A, 250VAC, general purpose, 85°C	$6x10^3$
V23092-*****-A301, -A801	A/B	B300, 85°C	$6x10^3$
V23092-*****-A301, -A801	A/B	R300, 85°C	$6x10^3$
EN60730-1			
V23092-*****-A302	A (NO)	3A (1.5A), 250VAC, 85°C	$100x10^3$
V23092-*****-A302, -A802	A (NO)	5A (1.5A), 250VAC, 85°C	$10x10^3$

Mechanical endurance, DC coil $10x10^6$ operations

Max. DC load breaking capacity



Electrical endurance



Coil Data

Coil voltage range	5 to 60VDC
Operative range, IEC 61810	2

Coil versions, DC coil

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10%[1]	Rated coil power mW
005	5	3.5	0.25	147	170
012	12	8.4	0.6	848	170
024	24	16.8	1.2	3390	170
048	48	33.6	2.4	10600[1]	217
060	60	42.0	3.0	20500[1]	176

1) Coil resistance ±15%.
All figures are given for coil without pre-energization, at ambient temperature +23°C.
Other coil voltages on request.

Coil operating range DC



Insulation Data

Initial dielectric strength	
between open contacts	$1000V_{rms}$
between contact and coil	$4000V_{rms}$
Clearance/creepage	
between contact and coil	≥6/8mm
Material group of insulation parts	IIIa
Tracking index of relay base	PTI250

04-2011, Rev. 0411
www.te.com
© 2011 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Slimline PCB Relay SNR (Continued)

Other Data

Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at www.te.com/customersupport/rohssupportcenter	
Ambient temperature	-40 to +85°C
Category of environmental protection IEC 61810	RTIII - wash tight
Vibration resistance (functional), form A (NO) / form B (NC)	10/5g
Shock resistance (functional), form A (NO) / form B (NC)	10/5g
Shock resistance (destructive)	30g
Terminal type	PCB-THT, plug-in
Mounting	PCB, socket
Weight	6g
Resistance to soldering heat THT IEC 60068-2-20	260°C/5s[2)]
Packaging unit	tube/20 pcs., box/1000 pcs.

2) for flat pack version selective soldering is recommended

Accessories

For details see datasheet	Accessories Slim Interface Relay SNR

勝 特 力 材 料 886-3-5753170
胜特力电子(上海) 86-21-34970699
胜特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw

PCB layout / terminal assignment

Bottom view on solder pins



1 form C contact (1 CO)



1 form A contact (1 NO)



Dimensions

Vertical version



Version for DIN-rail socket



Flat pack version[2)]



2) for flat pack version selective soldering is recommended

04-2011, Rev. 0411
www.te.com
© 2011 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Slimline PCB Relay SNR (Continued)

Product code structure

Typical product code	V23092	-A	1	005	-A	3	01

Type
V23092 Slimline PCB relay SNR

Version
A PCB, vertical version
B PCB, flat pack version
S Plug-in, vertical version

Version
1 Wash tight

Coil
Coil code: please refer to coil versions table

Contact system
A Standard

Contact material
2 $AgSnO_2$, gold plated
3 $AgSnO_2$
8 AgNi 90/10

Contact configuration
01 1 form C contact (1 CO)
02 1 form A contact (1 NO)

NO version with 8/8mm clearance and creepage and other types on request

勝 特 力 材 料 886-3-5753170
胜特力电子(上海) 86-21-34970699
胜特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw

Product code	Version	Contact arrangement	Contact material	Coil	Part number
V23092-A1005-A201	PCB	1 form C (CO) contact	$AgSnO_2$, gold plated	5VDC	1393236-1
V23092-A1005-A202	vertical version	1 form A (NO) contact			8-1415067-1
V23092-A1005-A301	wash tight	1 form C (CO) contact	$AgSnO_2$		1393236-2
V23092-A1005-A302		1 form A (NO) contact			9-1415067-1
V23092-A1005-A801		1 form C (CO) contact	AgNi 90/10		1-1415068-1
V23092-A1005-A802		1 form A (NO) contact			1415068-1
V23092-A1012-A201		1 form C (CO) contact	$AgSnO_2$, gold plated	12VDC	1393236-4
V23092-A1012-A202		1 form A (NO) contact			1393236-5
V23092-A1012-A301		1 form C (CO) contact	$AgSnO_2$		1393236-7
V23092-A1012-A302		1 form A (NO) contact			1393236-8
V23092-A1012-A801		1 form C (CO) contact	AgNi 90/10		1-1393236-3
V23092-A1012-A802		1 form A (NO) contact			2-1415068-1
V23092-A1024-A201		1 form C (CO) contact	$AgSnO_2$, gold plated	24VDC	2-1393236-1
V23092-A1024-A202		1 form A (NO) contact			2-1393236-2
V23092-A1024-A301		1 form C (CO) contact	$AgSnO_2$		2-1393236-4
V23092-A1024-A302		1 form A (NO) contact			2-1393236-5
V23092-A1024-A801		1 form C (CO) contact	AgNi 90/10		3-1393236-0
V23092-A1024-A802		1 form A (NO) contact			5-1415063-1
V23092-A1048-A201		1 form C (CO) contact	$AgSnO_2$, gold plated	48VDC	3-1393236-5
V23092-A1048-A202		1 form A (NO) contact			3-1393236-6
V23092-A1048-A301		1 form C (CO) contact	$AgSnO_2$		3-1393236-7
V23092-A1048-A302		1 form A (NO) contact			3-1393236-8
V23092-A1048-A801		1 form C (CO) contact	AgNi 90/10		3-1393236-9
V23092-A1048-A802		1 form A (NO) contact			3-1415068-1
V23092-S1005-A201	Plug-in	1 form C (CO) contact	$AgSnO_2$, gold plated	5VDC	1956024-9
V23092-S1005-A301	vertical version		$AgSnO_2$		1-1956024-0
V23092-S1012-A201	wash tight		$AgSnO_2$, gold plated	12VDC	1956024-1
V23092-S1012-A301			$AgSnO_2$		1956024-2
V23092-S1024-A201			$AgSnO_2$, gold plated	24VDC	1956024-3
V23092-S1024-A301			$AgSnO_2$		1956024-4
V23092-S1048-A201			$AgSnO_2$, gold plated	48VDC	1956024-5
V23092-S1048-A301			$AgSnO_2$		1956024-6
V23092-S1060-A201			$AgSnO_2$, gold plated	60VDC	1956024-7
V23092-S1060-A301			$AgSnO_2$		1956024-8

04-2011, Rev. 0411
www.te.com
© 2011 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.