产品编号 ： 02081001

Product Description ： MLX Female Crimp Terminal 42024, 14-20 AWG, Reel, Brass, Tin (Sn) Plating

系列号 ： 42024

状态 ： Active

Product Category ： Crimp Terminals

工程编号 ： 42024-1A1

Packaging Alternative ： 0002081002 (Bag)

文件和资源

图纸

图纸　002081001_sd.pdf

规格

产品规格　PS-42022-0001-001.pdf

测试摘要　TS-42022-0001-001.pdf

产物环境合规

合规

GADSL/IMDS	Compliant with Exemption 44
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

多部分行业合规性文件

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	活动
类别	Crimp Terminals
系列	42024
说明	MLX Female Crimp Terminal 42024, 14-20 AWG, Reel, Brass, Tin (Sn) Plating
应用	Power, Wire-to-Board, Wire-to-Wire
产品系列	MLX Power Connectors
产品名称	MLX
UPC	800753615878

物理

性别	女
材料 - 金属	Brass
材料 - 接合部位电镀	Tin
材料 - 终端电镀	Tin
净重	0.406/g
包装形式	Reel
最薄镀层 - 接合部位	0.508µm
最薄镀层 - 端接	0.508µm
终端界面类型	Crimp or Compression
导线绝缘直径	1.52-3.30mm
线径规格 (AWG)	14, 16, 18, 20
线缆尺寸mm²	不适用

进程

无铅	不适用

施工工具

全局

描述	产品编号
Extraction Tool for MLX 2.13mm Diameter Pin and Socket Crimp Terminals	0011010168
PremiumGrade Hand Crimp Tool for MLX Pin and Socket Terminals, 14-20 AWG	0638116800
FineAdjust Applicator for Crimp Terminals, 14-20 AWG Wire with 2.08-2.50mm Diameter Insulation	0639007500
FineAdjust Applicator for Crimp Terminals, 14-20 AWG Wire with 2.65-3.30mm Diameter Insulation	0639009800
FineAdjust Applicator for Crimp Terminals, 14-20 AWG Wire with 2.41-2.95mm Diameter Insulation	0639009900
T2 Terminator for MLX Crimp Terminals, 14-20 AWG	0639107500
T2 Terminator Tooling Die for Crimp Terminals, 14-20 AWG Wire	0639109800
T2 Terminator Tooling Die for Crimp Terminals, 14-20 AWG Wire	0639109900