



产品编号：5023520201

系列号：502352

Product Category：PCB Headers and Receptacles

Product Description：DuraClik Wire-to-Board Header, Single Row, Right-Angle, 2 Circuits, Tin (Sn) Plating, Black

状态：Active

文件和资源

图纸

图纸 5023520201_sd.pdf

3D 模型和设计文件

3D模型 5023520201_stp.zip

规格

产品规格 PS-502351-001-001.pdf

产物环境合规

合规

GADSL/IMDS	Compliant with Exemption 44; 33
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

产品详情

常规

状态	活动
类别	PCB Headers and Receptacles
系列	502352
说明	DuraClik Wire-to-Board Header, Single Row, Right-Angle, 2 Circuits, Tin (Sn) Plating, Black
应用	Automotive, Signal, Wire-to-Board
个评论	The Operating Temperature Range when used with DuraClik series 502351 is -40° C to +105° C. It is -40° C to 125° C when used with DuraClik ISL series 560123 or TPA series 505151.
元件类型	PCB Header
产品系列	DuraClik Connector System
产品名称	DuraClik
UPC	887191427317

机构

UL	E29179
----	--------

电气

每触点最大电流	3.0A
电压 - 最大	125V

物理

断开	否
回路数（已载入）	2
电路数（最多）	2
颜色-树脂	黑色
耐用性(插拔次数) - 最多次数	30
先接后断	否
阻燃性	SC-0
符合灼热丝规范	否

插接极性	是
锁定插接部位	是
插配长度	6.40mm
材料 - 金属	Copper Alloy
材料 - 接合部位电镀	Tin
材料 - 树脂	Polyamide
净重	0.402/g
行数	1
方向	Right Angle
包装形式	Embossed Tape on Reel
PCB 定位器	否
PCB 保持力	是
间距 - 插配接口	2.00mm
有极性的插配件	是
PCB 极性	是
可堆叠的	否
运行温度范围	-40° to +105° C
终端界面类型	Surface Mount

进程








最长持续时间	40
无铅	REFLOW
最大周期	1
最高温度	255

可配插/可连接使用的产品

可配插部件

描述	产品编号
DuraClik Single Row Receptacle Housings	<u>502351</u>
DuraClik TPA Single Row Receptacle Housings	<u>505151</u>
DuraClik ISL Single Row Receptacle Housings	<u>560123</u>


This document was generated on Jun 04, 2024











- 注記
NOTES
- 材質
ハウジング：耐熱性ナイロンUL94V-0
ピン：銅合金、ニッケル下地、錫メッキ、金メッキ
フィッティングネール：銅合金、ニッケル下地、錫メッキ
MATERIAL
HOUSING:POLYAMIDE UL94V-0
PIN: COPPER ALLOY, GOLD OR TIN OVER NICKEL PLATE.
FITTING NAIL: COPPER ALLOY, TIN OVER NICKEL PLATE.
 - 色：ナチュラル、黒、赤、青
COLOR:NATURAL, BLACK, RED, BLUE
 - 嵌合相手
ハウジング：502351-**0*
錫メッキ端子：50212-8*00,50372-8*00,560085-0101
金メッキ端子：56161-8*81
MATES WITH
HOUSING:502351-**0*
SN PLATING TERMINAL:50212-8*00,50372-8*00,560085-0101
AU PLATING TERMINAL:56161-8*81
 - エンボス梱包品の詳細はSD-502352-002参照
DETAILED TAPING PACKAGE, SEE SD-502352-002.
 - ELV及びRoHS適合
ELV AND RoHS COMPLIANT
 - 半田付け面のコプラナリティ：0.1mm MAX.
CO-PLANARITY OF SOLDERING TAILS TO BE 0.1mm MAX.


- 7.一般公差
GENERAL TOLERANCES
10 UNDER: ±0.2
10 OVER 30 UNDER: ±0.25
30 OVER: ±0.3
ANGULAR: ±3°

INITIAL REVISION:		
DRWN	SHSHIBATA	2007/12/18
CHECK	HKOMATSU	2007/12/18
APPR	AKANESHIGE	2007/12/18

FUNCTIONAL SYMBOLS FA = 0 FB = 0 FC = 0 DIVISIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION												
	DIMENSION UNITS		SCALE		CURRENT REV DESC: For fixing wrong view of 6ckt			<div>molex</div> 2.0MM PITCH W/B CONN. WAFER ASSY R/A SMT					
	mm		5:1										
	GENERAL TOLERANCES (UNLESS SPECIFIED)												
	ANGULAR TOL ± 0.5°												
	4 PLACES ±												
	3 PLACES ±		STATUS: Production DRWN: Hideo Yoneyama 2024-05-14 CHK'D: Hiromichi Komatsu 2024-05-16 APPR: Takashi Iida 2024-05-16			PRODUCT SALES DRAWING							
	2 PLACES ±												
	1 PLACE ±												
	0 PLACES ±												
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS													
THIRD ANGLE PROJECTION		DRAWING		SERIES		DOCUMENT NUMBER		DOC TYPE		DOC PART		REVISION	
		A3-SIZE		502352		SD-502352-001		PSD		001		L4	
						MATERIAL NUMBER		CUSTOMER				SHEET NUMBER	
						SEE CHART		GENERAL MARKET				1 OF 4	



INITIAL REVISION:		
DRWN	SHSHIBATA	2007/12/18
CHECK	HKOMATSU	2007/12/18
APPR	AKANESHIGE	2007/12/18

FUNCTIONAL SYMBOLS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
<div><div><div><div>E_A</div><div>= 0</div></div><div><div>E_C</div><div>= 0</div></div><div><div>E_F</div><div>= 0</div></div></div><div>DIVISIONAL SYMBOLS</div></div>		DIMENSION UNITS		SCALE		CURRENT REV DESC: For fixing wrong view of 6ckt							
		mm		4:1									
		GENERAL TOLERANCES (UNLESS SPECIFIED)											
		ANGULAR TOL ± 0.5°											
		4 PLACES		±									
3 PLACES		±		<div>STATUS: Production</div> <div>DRWN: Hideo Yoneyama</div> <div>2024-05-14</div> <div>CHK'D: Hiromichi Komatsu</div> <div>2024-05-16</div> <div>APPR: Takashi Iida</div> <div>2024-05-16</div>									
2 PLACES		±											
1 PLACE		±											
0 PLACES		±											
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS													
		THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER	
				A3-SIZE		502352		SEE CHART		GENERAL MARKET		3 OF 4	

<div>molex</div>				
2.0MM PITCH W/B CONN. WAFER ASSY R/A SMT				
PRODUCT SALES DRAWING				
DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION
SD-502352-001		PSD	001	L4
MATERIAL NUMBER		CUSTOMER		SHEET NUMBER
SEE CHART		GENERAL MARKET		3 OF 4

注記
NOTES

1. 製品番号

ナチュラル・錫めっき: 502352-**00

ナチュラル・金めっき: 502352-**10

黒・錫めっき: 502352-**01

赤・錫めっき: 502352-**02

青・錫めっき: 502352-**03

詳細寸法については、製品単体図面を参照下さい。

PART NO.

NATURAL Sn Plating: 502352-**00

NATURAL Au Plating: 502352-**10

BLACK Sn Plating: 502352-**01

RED Sn Plating: 502352-**02

BLUE Sn Plating: 502352-**03

SEE SALES DRAWING FOR CONNECTOR

2. 梱包数量: 700個/リール

NUMBER OF CONNECTORS 700PCS/REEL

3. リードテープ長さ

LEAD TAPE LENGHT

4. 材料

MATERIAL

キャリアテープ: ポリスチレン

CARRIER TAPE: POLYSTYRENE

トップテープ: PET, PE, PEF

TOP TAPE: PET, PE, PEF

リール: ポリスチレン

REEL: POLYSTYRENE

5. 一般公差


GENERAL TOLERANCES


10 UNDER: ± 0.2

10 OVER 30 UNDER: ± 0.25

30 OVER: ± 0.3

ANGULAR: $\pm 1^\circ$



THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
DIMENSION UNITS		SCALE		CURRENT REV DESC:				<div>molex</div>	
mm		NTS							
<div>GENERAL TOLERANCES (UNLESS SPECIFIED)</div>				<div>EC NO: 629663</div> <div>DRWN: MSATO082019/12/26</div> <div>CHK'D: HIJIMA2019/12/27</div> <div>APPR: TOSADA2019/12/27</div> <div>INITIAL REVISION:</div> <div>DRWN: SHSHIBATA2007/06/19</div> <div>APPR: AKANESHIGE2007/06/19</div>				<div>2.0MM PITCH W/B CONN.</div> <div>WAFER ASSY EMBOSSED TAPE PACKAGE</div>	
ANGULAR TOL ± °									
4 PLACES ±									
3 PLACES ±									
2 PLACES ±									
1 PLACE ±				<div>PRODUCT CUSTOMER DRAWING</div> <div>DOCUMENT NUMBERSD-502352-002</div> <div>DOC TYPEPSD</div> <div>DOC PART001</div> <div>REVISIONK2</div>					
0 PLACES ±									
<div>DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</div>				<div>THIRD ANGLE PROJECTION</div> <div></div>		<div>DRAWING</div> <div>A3-SIZE</div>		<div>SERIES</div> <div>502352</div>	
				<div>MATERIAL NUMBER</div> <div>SEE CHART</div>		<div>CUSTOMER</div> <div>GENERAL MARKET</div>		<div>SHEET NUMBER</div> <div>1 OF 2</div>	

