



SIGN	DATE	DESCRIPTION	APPROVER
1	2/06'06	Part No. changed	Tony
2	07/12'10	Recommended P.C.B Layout is changed	Aaron
3	11/08'12	Change the screw plating specification	Jacky

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!









RECOMMENDED PCB LAYOUT 2

MATERIALS ELECTRICAL

RATED VOLTAGE & CURRENT:	300 V, 20 A
WITHSTAND VOLTAGE:	AC 2000 V/Min
INSULATION RESISTANCE:	1000 MΩ OR MORE AT DC 500 V
OPERATING TEMPERATURE RANG:	-40 °C ~+115 °C
SCREW TORQUE VALUE:	8.8 Lb-In.
WIRE RANGE:	22 - 12 AWG
1) MOLDED PARTS:	PA 66, UL 94 V-0 BLACK
2) TERMINAL:	BRASS, 0.8t, Tin PLATED
3 3) TERMINAL SCREWS:	STEEL, M3
APPROVAL:	cULus
1 PART NO.:	
Critical dimension:	℄

YK 421 xx 0 x x 00G

- RoHS compliant (lead<4%) in copper Alloy
- NO. OF POLES
  - 02: 2 POLES
  - 03: 3 POLES
  - 04: 4 POLES
  - :
  - 30: 30 POLES
- MARK
  - 0: "@" MARK
  - 1: "ANY" MARK
- TERMINAL & SCREW PLATED
  - 0: TERMINAL & SCREW: G/F
  - 3 1: TERMINAL: G/F, SCREW: Zinc
  - 2: TERMINAL: Sn, SCREW: G/F
  - 3 3: TERMINAL: Sn, SCREW: Zinc

勝 特 力 材 料 886-3-5753170
胜特力电子(上海) 86-21-34970699
胜特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw

POLE	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Dim A		18.22	26.47	34.72	42.97	51.22	59.47	67.72	75.97	84.22	92.47	100.72	108.97	117.22	125.47	133.72
Dim B		8.25	16.50	24.75	33.00	41.25	49.50	57.75	66.00	74.25	82.50	90.75	99.00	107.25	115.50	123.75
Tol	±0.30								±0.40							
POLE	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
Dim A	141.97	150.22	158.47	166.72	174.97	183.22	191.47	199.72	207.97	216.22	224.47	232.72	240.97	249.22	257.47	265.72
Dim B	132.00	140.25	148.50	156.75	165.00	173.25	181.50	189.75	198.00	206.25	214.50	222.75	231.00	239.25	247.50	255.75
Tol	±0.50								±0.60							

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	YK-421 W/O Flange Series				
PART NO.	YK421xx0xx00G			DWG NO.	8YK0001-421
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Jacky 2012.11.08	Jacky 2012.11.08	UNIT: mm SCALE: NONE SHEET: 01/01 REV.: E	

Tolerance	
X.	±0.50
X.X	±0.30
X.XX	±0.10
X°	±1°