



# NOTE:

MAXIMUM ELECTRICAL RATING: 105 °C 600 VOLTS

## BC1A

1. WIRE RANGE: AWG 22-16/0.5-1.5mm<sup>2</sup> : 19 AMPERE MAX.

2. INSULATED COLOR: RED

## BC2A

1. WIRE RANGE: AWG 16-14/1.5-2.5mm<sup>2</sup> : 27 AMPERE MAX.

2. INSULATED COLOR: BLUE

## BC5A

1. WIRE RANGE: AWG 12-10/4-6mm<sup>2</sup> : 48 AMPERE MAX.

2. INSULATED COLOR: YELLOW

| 產品編號<br>ITEM NO. | L<br>mm | F<br>mm | D<br>mm | d<br>mm |
|------------------|---------|---------|---------|---------|
| BC1A             | 26.0    | 15.0    | 4.1     | 1.7     |
| BC2A             | 26.0    | 15.0    | 4.5     | 2.3     |
| BC5A             | 27.0    | 15.0    | 6.5     | 3.4     |



| 認可 APPROVALS |      | 第三視角<br>THIRD VIEW | MATERIAL          | 單位UNIT  |
|--------------|------|--------------------|-------------------|---------|
| 製圖 DRAFT:    | Den  |                    | INSULATION: NYLON | mm      |
| 設計 DESIGN:   | 劉' r |                    | MATERIAL: COPPER  | 比例SCALE |
| 核可 CHECKED:  | Chen |                    | TIN PLATING       |         |

勝特力材料 886-3-5753170  
 勝特力電子(上海) 86-21-54151736  
 勝特力電子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)