



ITEM NO.	conductor(mm2)	L	F	ØD	Ød1
☐ CT0.5-8	2x0.5	15.0 .591	8.0 .315	1.8 .071	3.0*5.2
☐ CT0.75-8	2X0.75	15.0 .591	8.0 .315	2.1 .083	3.3*5.5
☐ CT0.75-10	2X0.75	17.0 .669	10.0 .394	2.1 .083	3.3*5.5
☐ CT1.0-8	2x1.0	15.0 .591	8.0 .315	2.35 .093	4.0*6.0
☐ CT1.0-10	2x1.0	17.0 .669	10.0 .394	2.35 .093	4.0*6.0
☐ CT1.5-8	2x1.5	16.0 .630	8.0 .315	2.6 .102	4.2*7.2
☐ CT1.5-12	2x1.5	20.0 .787	12.0 .472	2.6 .102	4.2*7.2
☐ CT2.5-10	2x2.5	18.5 .728	10.0 .394	3.2 .126	4.8*8.4
☐ CT2.5-13	2x2.5	21.5 .846	13.0 .512	3.2 .126	4.8*8.4
☐ CT4-12	2x4.0	23.0 .906	12.0 .472	4.1 .161	5.7*9.6
☐ CT6-14	2x6.0	26.0 1.024	14.0 .551	5.2 .205	7.7*10.8
☐ CT10-14	2x10.0	26.5 1.043	14.0 .551	6.8 .268	8.6*13.8
☐ CT16-14	2x16.0	31.5 1.240	14.0 .551	8.9 .350	10.6*19.6

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)