


裸銅管 EN25-12 管形裸端子 銅管 冷壓 銅連接管 GT 型
EN35-16 裸銅管 管形裸端子 銅管 冷壓 銅連接管 GT 型



勝特力材料 886-3-5773766
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



端头材质: 鍍錫紫銅管

电线范围 A.W.G mm ²	型号	尺寸				使用压接 工具型号
		L	D	C	W	
		mm	mm	mm	mm	
24 A.W.G 0.3mm ²	EN0306	6.0	1.1	0.8	1.5	
	EN0308	8.0				
22 A.W.G 0.5mm ²	EN0505	5.0	1.3	1.0	1.7	KT-05WF 使用0.5钳口
	EN0506	6.0				
	EN0508	8.0				
	EN0510	10.0				
	EN0512	12.0				
20 A.W.G 0.75mm ²	EN7506	6.0	1.5	1.2	1.9	KT-05WF 使用0.75钳口
	EN7508	8.0				
	EN7510	10.0				
	EN7512	12.0				
	EN7515	15.0				
18 A.W.G 1.0mm ²	EN1006	6.0	1.7	1.4	2.2	KT-05WF 使用1.0钳口
	EN1008	8.0				
	EN1010	10.0				
	EN1012	12.0				
	EN1015	15.0				
16 A.W.G 1.5mm ²	EN1507	7.0	2.0	1.7	2.5	KT-05WF 使用1.5钳口
	EN1508	8.0				
	EN1510	10.0				
	EN1512	12.0				
	EN1515	15.0				
14 A.W.G 2.5mm ²	EN2506	6.0	2.6	2.3	3.3	KT-05WF 使用2.5钳口
	EN2507	7.0				
	EN2508	8.0				
	EN2510	10.0				
	EN2512	12.0				
	EN2515	15.0				
	EN2518	18.0				
12 A.W.G 4mm ²	EN4009	9.0	3.2	2.8	3.9	KT-05WF 使用4.0钳口
	EN4010	10.0				
	EN4012	12.0				
	EN4015	15.0				
	EN4018	18.0				

烟头材质: 镀锌紫铜管

电线范围 A.W.G mm²	型号	尺寸				使用压接 工具型号
		L	D	C	W	
		mm	mm	mm	mm	
10 A.W.G 6mm²	EN6006	6.0	3.9	3.5	4.7	KT-05WF 使用6.0钳口
	EN6010	10.0				
	EN6012	12.0				
	EN6015	15.0				
	EN6018	18.0				
8 A.W.G 10mm²	EN10-12	12.0	4.9	4.5	5.8	KT-16WF 使用10钳口
	EN10-15	15.0				
	EN10-16	16.0				
	EN10-18	18.0				
	EN10-12L	12.0	5.5	5.0	6.5	
6 A.W.G 16mm²	EN16-12	12.0	6.2	5.8	7.2	KT-16WF 使用16钳口
	EN16-15	15.0				
	EN16-16	16.0				
	EN16-18	18.0				
	EN16-20	20.0				
	EN16-22	22.0				
	EN16-25	25.0				
4 A.W.G 25mm²	EN16-30	30.0	7.9	7.5	9.1	使用25钳口
	EN25-12	12.0				
	EN25-15	15.0				
	EN25-16	16.0				
	EN25-18	18.0				
	EN25-20	20.0				
	EN25-22	22.0				
2 A.W.G 35mm²	EN25-25	25.0	8.7	8.3	10.2	使用35钳口
	EN25-30	30.0				
	EN35-12	12.0				
	EN35-15	15.0				
	EN35-16	16.0				
	EN35-18	18.0				
	EN35-20	20.0				
1/0 A.W.G 50mm²	EN35-25	25.0	10.9	10.3	12.7	使用50钳口
	EN35-30	30.0				
	EN50-18	18.0				
	EN50-20	20.0				
	EN50-22	22.0				
2/0 A.W.G 70mm²	EN50-25	25.0	14.3	13.5	15.8	
	EN70-20	20.0				
	EN70-22	22.0				
3/0 A.W.G 95mm²	EN70-25	25.0	15.6	14.8	17.3	
	EN90-25	25.0				
	EN90-30	30.0				
4/0 A.W.G 120mm²	EN90-32	32.0	17.7	16.7	20.0	
	EN120-30	30.0				
	EN120-32	32.0				
	EN120-34	34.0				
250/300 MCM A.W.G 150mm² MCM	EN120-38	38.0	20.6	19.6	23.0	
	EN150-32	32.0				
	EN150-34	34.0				
250/300 A.W.G 185mm²	EN150-38	38.0	20.6	19.6	23.0	
	EN185-32	32.0				
	EN185-40	40.0				

