

NON-INSULATED SPADE TERMINALS

1. TERMINAL MATERIAL : COPPER
2. BRAZED SEAM
3. PLATING : ELECTRO TIN PLATED

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



S1-4SNB



S2-4LNB




S3-4NB



S5-5NB



S8-5NB



1~8mm²

WIRE RANGE AWG / mm ²	ITEM NO.	UL	STUD SIZE d2	DIMENSIONS inch (mm)						
				B	F	L	E	D	d1	t
22-16 AWG 1.5-1.5 mm ²	S1-3SNB		#4 (3.2)	.197 (5.0)	.248 (6.3)	.630 (16.0)	.197 (5.0)	.134 (3.4)	.067 (1.7)	.030 (0.75)
	S1-3NB		#4 (3.2)	.228 (5.8)	.248 (6.3)	.630 (16.0)				
	✓ S1-3.5SNB		#6 (3.7)	.228 (5.8)	.248 (6.3)	.630 (16.0)				
	✓ S1-3.5MNB		#6 (3.7)	.252 (6.4)	.248 (6.3)	.614 (15.6)				
	✓ S1-3.5LNB		#6 (3.7)	.283 (7.2)	.248 (6.3)	.630 (16.0)				
	✓ S1-4SNB		#8 (4.3)	.252 (6.4)	.248 (6.3)	.614 (15.6)				
	✓ S1-4MNB		#8 (4.3)	.283 (7.2)	.248 (6.3)	.630 (16.0)				
	✓ S1-4LNB		#8 (4.3)	.315 (8.0)	.276 (7.0)	.630 (16.0)				
	✓ S1-5SNB		#10 (5.3)	.315 (8.0)	.276 (7.0)	.630 (16.0)				
	✓ S1-5LNB		#10 (5.3)	.374 (9.5)	.276 (7.0)	.630 (16.0)				
	✓ S1-6SNB		1/4 (6.5)	.374 (9.5)	.276 (7.0)	.630 (16.0)				
	✓ S1-6LNB		1/4 (6.5)	.472 (12.0)	.433 (11.0)	.874 (22.2)				
18-14 AWG 1.5-2.5 mm ²	S1-8NB		5/16 (8.4)	.472 (12.0)	.433 (11.0)	.874 (22.2)	.197 (5.0)	.161 (4.1)	.091 (2.3)	.031 (0.8)
	✓ S2-3SNB		#4 (3.2)	.197 (5.0)	.248 (6.3)	.630 (16.0)				
	✓ S2-3NB		#4 (3.2)	.228 (5.8)	.248 (6.3)	.630 (16.0)				
	✓ S2-3.5SNB		#6 (3.7)	.228 (5.8)	.248 (6.3)	.630 (16.0)				
	✓ S2-3.5MNB		#6 (3.7)	.252 (6.4)	.248 (6.3)	.630 (16.0)				
	✓ S2-3.5LNB		#6 (3.7)	.283 (7.2)	.256 (6.5)	.638 (16.2)				
	✓ S2-4SNB		#8 (4.3)	.252 (6.4)	.248 (6.3)	.630 (16.0)				
	✓ S2-4MNB		#8 (4.3)	.283 (7.2)	.256 (6.5)	.638 (16.2)				
	✓ S2-4LNB		#8 (4.3)	.335 (8.5)	.287 (7.3)	.669 (17.0)				
	✓ S2-5SNB		#10 (5.3)	.335 (8.5)	.287 (7.3)	.669 (17.0)				
	✓ S2-5LNB		#10 (5.3)	.374 (9.5)	.287 (7.3)	.669 (17.0)				
	✓ S2-6SNB		1/4 (6.5)	.374 (9.5)	.287 (7.3)	.669 (17.0)				
14-12 AWG 2.5-4 mm ²	✓ S2-6LNB		1/4 (6.5)	.472 (12.0)	.433 (11.0)	.874 (22.2)	.236 (6.0)	.197 (5.0)	.110 (2.8)	.039 (1.0)
	✓ S2-8NB		5/16 (8.4)	.472 (12.0)	.433 (11.0)	.874 (22.2)				
	✓ S3-3.5NB		#6 (3.7)	.315 (8.0)	.276 (7.0)	.720 (18.3)				
	✓ S3-4NB		#8 (4.3)	.315 (8.0)	.276 (7.0)	.720 (18.3)				
	✓ S3-5NB		#10 (5.3)	.315 (8.0)	.276 (7.0)	.720 (18.3)				
	✓ S3-6NB		1/4 (6.5)	.472 (12.0)	.358 (9.1)	.846 (21.5)				
12-10 AWG 4-6 mm ²	✓ S5-3.5SNB		#6 (3.7)	.283 (7.2)	.295 (7.5)	.736 (18.7)	.236 (6.0)	.220 (5.6)	.134 (3.4)	.039 (1.0)
	✓ S5-3.5LNB		#6 (3.7)	.335 (8.5)	.295 (7.5)	.736 (18.7)				
	✓ S5-4SNB		#8 (4.3)	.335 (8.5)	.295 (7.5)	.736 (18.7)				
	✓ S5-4LNB		#8 (4.3)	.374 (9.5)	.295 (7.5)	.736 (18.7)				
	✓ S5-5NB		#10 (5.3)	.374 (9.5)	.295 (7.5)	.736 (18.7)				
	✓ S5-6SNB		1/4 (6.5)	.374 (9.5)	.295 (7.5)	.736 (18.7)				
	✓ S5-6LNB		1/4 (6.5)	.472 (12.0)	.472 (12.0)	.972 (24.7)				
	✓ S5-8NB		5/16 (8.4)	.531 (13.5)	.413 (10.5)	.925 (23.5)				
8 AWG 8 mm ²	✓ S8-4NB		#8 (4.3)	.323 (8.2)	.319 (8.1)	.807 (20.5)	.335 (8.5)	.283 (7.2)	.177 (4.5)	.047 (1.2)
	✓ S8-5NB		#10 (5.3)	.354 (9.0)	.319 (8.1)	.807 (20.5)				
	✓ S8-6NB		1/4 (6.5)	.425 (10.8)	.339 (8.6)	.886 (22.5)				