勝 特 力 材 料 886-3-5753170
胜特力电子(上海) 86-21-34970699
胜特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw

WAGO INNOVATIVE CONNECTIONS

Item no.:	235-402/331-000
Product description:	1-CONDUCTOR PCB TERMINAL STRIP 2 SOLDER PINS / POLE 2 POLE PIN SPACING 5/5.08 MM / 0.2 IN WITH PUSH BOTTONS



Produkt kann von Bild abweichen / product may differ

Packing unit 420 4*105 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	1.635 g
Color	gray
No. of connection Points	2
No. of potentials	2
pole count	2
Height	15.5 mm
Height	0.61 in
Width	11.5 mm
Width	0.453 in
Depth	12.5 mm
Depth	0.492 in
Pin spacing from	5 mm
Pin spacing up to	5.08 mm
Pin spacing from	0.197 in
Pin spacing up to	0.2 in
Pollution degree	2
Measured voltage EN	320 V

Measured shock voltage	4 kV
Current intensity EN	17.5 A
Pollution degree	2
Measured voltage EN	630 V

Measured shock voltage	4 kV
Current intensity EN	17.5 A
Cross section [mm²]	0.2 - 1.5 mm²
Wiring method	solid
Cross section [mm²]	0.25 - 0.75 mm²
Wiring method	fine-stranded (with ferrule and plastic collar)
Cross section [mm²]	0.25 - 0.75 mm²
Wiring method	fine-stranded (with ferrule, without plastic collar)
Cross section [AWG]	20 - 14 AWG
Strip length from	9 mm
Strip length to	10 mm
Material group	I
Contact material	Electrolytic copper (Ecu)
Contact surface	tin-plated

勝 特 力 材 料 886-3-5753170
胜特力电子(上海) 86-21-34970699
胜特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw

Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
235-402/331-000	CCA	NL6309	250	10	0,5-2,5
235-402/331-000	CSA	154112-1673956	300	15	20-14
235-402/331-000	KEMA	2110204.16	250	10	0,5-2,5
235-402/331-000	UR	E45172	300	10	20-14

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected