

OSRAM DULUX S

Short CFLni, with 2-pin base for CCG operation

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



Areas of application

- Ideal for cost-effective creative illumination and decoration
- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants

Product benefits

- Extremely economical
- Good quality of light
- Extremely low profile
- Long service life
- Improved maintenance

Product features

- Average life: 10,000 h
- Color rendering index R_a for lamps with white light: 80...89
- Also available in red, green and blue
- Short and compact pin-base lamps with single-turn tubes
- Single-ended two-pin plug-in G23 base



Product family datasheet



Product line drawing

Base

Product family datasheet

Technical data

Product description	Nominal wattage	Nominal luminous flux	Color temperature	Nominal lamp life time	Base (standard designation)	Rated lamp efficacy (standard condition)
DULUX S 5 W/827	5 W	257 lm	2700 K	10000 h	G23	46 lm/W
DULUX S 5 W/840	5 W	250 lm	4000 K	10000 h	G23	48 lm/W
DULUX S 7 W/827	7 W	400 lm	2700 K	10000 h	G23	57 lm/W
DULUX S 7 W/830	7 W	400 lm	3000 K	10000 h	G23	57 lm/W
DULUX S 7 W/840	7 W	400 lm	4000 K	10000 h	G23	57 lm/W
DULUX S 9 W/827	9 W	600 lm	2700 K	10000 h	G23	69 lm/W
DULUX S 9 W/830	9 W	600 lm	3000 K	10000 h	G23	69 lm/W
DULUX S 9 W/835 G23	9 W	600 lm	3500 K	10000 h	G23	69 lm/W
DULUX S 9 W/840	9 W	600 lm	4000 K	5000 h	G23	
DULUX S 9 W/865 G23	9 W	570 lm	6500 K	10000 h	G23	66 lm/W
DULUX S 11 W/827	11 W	900 lm	2700 K	10000 h	G23	76 lm/W
DULUX S 11 W/830	11 W	900 lm	3000 K	10000 h	G23	76 lm/W
DULUX S 11 W/840	11 W	900 lm	4000 K	10000 h	G23	76 lm/W
DULUX S 9 W/60	9 W	400 lm		10000 h	G23	52 lm/W
DULUX S 9 W/66	9 W	800 lm		10000 h	G23	92 lm/W
DULUX S 9 W/67	9 W	200 lm		10000 h	G23	21 lm/W

Product description	Color rendering index Ra	Luminous flux at 25 °C	Light color	Service life	Appropriate disposal acc. to WEEE	Nominal voltage
DULUX S 5 W/827	80...89	250 lm	827	6500 h	Yes	

Product family datasheet

Product description	Color rendering index Ra	Luminous flux at 25 °C	Light color	Service life	Appropriate disposal acc. to WEEE	Nominal voltage
DULUX S 5 W/840	80...89	250 lm	840	6500 h	Yes	
DULUX S 7 W/827	80...89	400 lm	827	6500 h	Yes	
DULUX S 7 W/830	80...89	400 lm	830	6500 h	Yes	
DULUX S 7 W/840	80...89	400 lm	840	6500 h	Yes	
DULUX S 9 W/827	80...89	600 lm	827	6500 h	Yes	
DULUX S 9 W/830	80...89	600 lm	830	6500 h	Yes	
DULUX S 9 W/835 G23	80...89	600 lm	835	6500 h	Yes	
DULUX S 9 W/840	80...89	600 lm	840	6500 h	Yes	220 V
DULUX S 9 W/865 G23	80...89	570 lm	865	6500 h	Yes	
DULUX S 11 W/827	80...89	900 lm	827	6500 h	Yes	
DULUX S 11 W/830	80...89	900 lm	830	6500 h	Yes	
DULUX S 11 W/840	80...89	900 lm	840	6500 h	Yes	
DULUX S 9 W/60		400 lm	60		Yes	
DULUX S 9 W/66		800 lm	66		Yes	
DULUX S 9 W/67		200 lm	67		Yes	

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)