

Detailed Specifications & Technical Data**1505A Coax - Precision Video Cable for Analog and Digital**

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

For more information please
 call

1-800-Belden1

See Put-ups and Colors

**Description:**

20 AWG Solid .032" Bare Copper conductor, Gas-injected Foam HDPE Insulation, Duofoil® and a 95% Tinned Copper Braid Shield, PVC Jacket.

PHYSICAL CHARACTERISTICS:**CONDUCTOR:**

Number of Coax	1
Total Number of Conductors	1
RG Type	59/U
AWG	20
Stranding	solid
Conductor Diameter	.032 in.
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	Gas-injected FHDPE - Foam High Density Polyethylene
Insulation Diameter	.145 in.

OUTER SHIELD:

Outer Shield Type	Tape/Braid
-------------------	------------

Outer Shield Material :

Layer Number	Trade Name	Type	Material	% Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	Tinned Copper	95

Outer Shield %Coverage	100 %
------------------------	-------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.234 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-30°C To +75°C
Bulk Cable Weight	31 lbs/1000 ft.
Max. Recommended Pulling Tension	47 lbs.

Detailed Specifications & Technical Data

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



1505A Coax - Precision Video Cable for Analog and Digital

Min. Bend Radius (Install) 2.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification CMR

CEC/C(UL) Specification CMG

FLAME TEST:

UL Flame Test 1666 Vertical Shaft

CSA Flame Test FT4

SUITABILITY:

Suitability - Indoor All colors

Suitability - Outdoor Black jacket only

Suitability - Aerial Black jacket only when supported by a messenger wire

PLENUM/NON-PLENUM:

Plenum (Y/N) N

Plenum Number 1506A

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance 75 +/- 1.5 Ohms

Nom. Inductance 0.107 µH/ft

Nom. Capacitance Conductor to Shield 16.3 pF/ft

Nominal Velocity of Propagation 83 %

Nominal Delay 1.22 ns/ft

Nom. Conductor DC Resistance @ 20 Deg. C 10.0 Ohms/1000 ft

Nominal Outer Shield DC Resistance 3.8 Ohms/1000 ft

Minimum Return Loss :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Minimum Return Loss (dB)
		5	850	23
		851	3000	21

Nom. Attenuation :

Detailed Specifications & Technical Data

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



1505A Coax - Precision Video Cable for Analog and Digital

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
Nominal Attenuation	1			.29
	3.58			.55
	5			.63
	7			.74
	10			.87
	67.5			2.05
	71.5			2.1
	88.5			2.2
	100			2.3
	135			2.7
	143			2.8
	180			3.1
	270			3.8
	360			4.4
	540			5.5
	720			6.4
	750			6.5
	1000			7.6
	1500			9.3
	2000			10.9
	2250			11.6
	3000			13.4

Max. Operating Voltage - UL

300 V RMS

NOTES:

Notes

Also available in bundled versions. See 7794A through 7798A. 100% Sweep tested .5 MHz to 3 GHz. Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination. Return Loss tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1505A 0011000	#20 PE/GIFHDPE SH FR PVC	1000	35	BROWN	C
1505A 0015000	#20 PE/GIFHDPE SH FR PVC	5000	165	BROWN	C N
1505A 0021000	#20 PE/GIFHDPE SH FR PVC	1000	35	RED	C
1505A 002500	#20 PE/GIFHDPE SH FR PVC	500	17.5	RED	C
1505A 0025000	#20 PE/GIFHDPE SH FR PVC	5000	165	RED	C N
1505A 0031000	#20 PE/GIFHDPE SH FR PVC	1000	35	ORANGE	C
1505A 0035000	#20 PE/GIFHDPE SH FR PVC	5000	165	ORANGE	C N

Detailed Specifications & Technical Data

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



1505A Coax - Precision Video Cable for Analog and Digital

1505A 0041000	#20 PE/GIFHDPE SH FR PVC	1000	35	YELLOW	C
1505A 0045000	#20 PE/GIFHDPE SH FR PVC	5000	165	YELLOW	C N
1505A 0061000	#20 PE/GIFHDPE SH FR PVC	1000	35	BLUE, LIGHT	C
1505A 006500	#20 PE/GIFHDPE SH FR PVC	500	17.5	BLUE, LIGHT	C
1505A 0065000	#20 PE/GIFHDPE SH FR PVC	5000	165	BLUE, LIGHT	C N
1505A 0071000	#20 PE/GIFHDPE SH FR PVC	1000	35	VIOLET	C
1505A 0075000	#20 PE/GIFHDPE SH FR PVC	5000	165	VIOLET	C N
1505A 0081000	#20 PE/GIFHDPE SH FR PVC	1000	35	GRAY	C
1505A 0085000	#20 PE/GIFHDPE SH FR PVC	5000	165	GRAY	C N
1505A 0091000	#20 PE/GIFHDPE SH FR PVC	1000	35	WHITE	C
1505A 0095000	#20 PE/GIFHDPE SH FR PVC	5000	165	WHITE	C N
1505A 0101000	#20 PE/GIFHDPE SH FR PVC	1000	35	BLACK	C
1505A 010500	#20 PE/GIFHDPE SH FR PVC	500	17.5	BLACK	C
1505A 0105000	#20 PE/GIFHDPE SH FR PVC	5000	165	BLACK	C N
1505A N3U1000	#20 PE/GIFHDPE SH FR PVC	1000	35	GREEN, MIL	C
1505A N3U5000	#20 PE/GIFHDPE SH FR PVC	5000	165	GREEN, MIL	C N

C = CRATE REEL PUT-UP.

N = FINAL PUT-UP LENGTH MAY VARY -0% TO +10% FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 10-22-2003

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.