


產品圖	導線截面	額定電流	額定電壓	尺寸
	0.5-1.5mm ²	17.5A	660V	10*31*39
	0.5-2.5mm ²	24A	660V	12*36*41
	0.75-2.5mm ²	32A	660V	12.5*42*34
	2.5-6mm ²	41A	660V	16*45*48.5
	4-10mm ²	57A	660V	18*51*50
	10-25mm ²	101A	660V	25*61*60
	0.5-1.5mm ²	17.5A	660V	19.5*31*39
	0.5-1.5mm ²	17.5A	660V	28.5*31*39
	0.5-1.5mm ²	17.5A	660V	46.5*31*39
	0.5-2.5mm ²	24A	660V	24.5*36*41
	0.5-2.5mm ²	24A	660V	36*36*41
	0.5-2.5mm ²	17.5A	660V	39*31*39
	0.75-1.5mm ²	17.5A	500V	44.5*44.5*7.5
	0.75-1.5mm ²	17.5A	500V	44.5*44.5*7.5*
	1.5-2.5mm ²	24A	500V	46.5*51.5*9.5
	1.5-2.5mm ²	24A	380V	49*70.5*16
	1.5-2.5mm ²	24A	380V	59*68.5*12
	6-10mm ²	57A	500V	54*46.5*16.5
	1-2.5mm ²	24A	660V	44*51.5*10
	4-10mm ²	57A	660V	63*73*18
	0.5-1.5mm ²	17.5A	660V	39*52*8
	0.5-2.5mm ²	25A	660V	12*36*41
	0.5-2.5mm ²	25A	660V	12.5*40*48.5
	10-25mm ²	25A	660V	25*61*60
	10-25mm ²	110A	600V	105*39*30
	14mm ²	60A	600V	56*43*32.5
	0.5-1.5mm ²	15A	600V	55.5*22*17.5
	0.5-1.5mm ²	15A	600V	12.8*22*17.5
	0.5-2.5mm ²	25A	600V	67*30*19
	6-10mm ²	60A	600V	230*26*3.3
	0.5-6mm ²	36A	600V	
	0.5-6mm ²	36A	600V	

勝 特 力 材 料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



0.75-1.5mm ²	15A	600V	8*32*31.5
4-6-10mm ²	60A	600V	16.5*50*36.5
1.5-6mm ²	30A	660V	13*38*28
10-25mm ²	100A	660V	21*64*46
0.75-1.5mm ²	17.5A	600V	8*32*31.5
10-16-25mm ²	101A	600V	19*50*43
2.5-25mm ²	10A	800V	
0.5-10mm ²	57A	500V	
0.2-4mm ²	32A	600V	
0.2-6mm ²	44A	500V	
0.2-2.5mm ²	16A	690V	
0.2-4mm ²	32A	500V	