



一般公差	
尺寸範圍	公差
0.5-6	±0.2
6-30	±0.4
30-120	±0.5
120-315	±1
315-1000	±1.6
1000-2000	±2.4

NO. POLES	MODEL NO.	SWITCH FUNCTION			TERMINAL QUANTITY
		POS.1	POS.1	POS.1	
SPST	5027	ON	NONE	OFF	2P
SPST	5025	ON	NONE	ON	3P
SPST	5025A	ON	OFF	ON	3P

SPECIFICATION

CONTACT RATING: 5 AMPS @120 V AC or 28 V DC.
2 AMPS @250 V AC or 0.4 AMPS @20 V AC or DC.
ELECTRICAL LIFE: 50,000 make-and-break cycles at full load.
CONTACT RESISTANCE: 10 mΩ max. initial @ 2-4 V DC.
100 mA, for both silver and gold plated contacts.

INSULATION RESISTANCE: 1,000 MΩ min.
DIELECTRIC STRENGTH: 1,000 V RMS @sea level.
OPERATING TEMPERATURE: -30°C to 130°C

勝特力電材超市-龍山店 886-3-5773766

勝特力電材超市-光復店 886-3-5729570

勝特力電子(上海) 86-21-34970699

勝特力電子(深圳) 86-755-83298787

<http://www.100y.com.tw>

母件編號

物料編號

單位 mm

比例

母件名稱

物料名稱

數量

1 PCS

搖頭 SW (3P)

承製廠

日期

990325