



產品資訊:
DULUX S 13 W/840



PDF



名稱: DULUX S 13 W/840

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Applications	
Suitable for indoor	Yes
General Description	
Lamp mercury content	1.4 mg
燈頭	GX23
資源回收	Yes
Technical - Electrical Data	
Rated lamp efficacy (HF data)	Under clarification by authority and standardization body
Rated lamp efficacy (standard condition)	61 lm/W
Operation mode LLMF/LSF	50 Hz
Rated wattage	13.4 W
中值功率(包裝)	13,4 W
Technical - Geometries	
Overall length	178.00 mm
直徑	12.00 mm
管徑 (毫米)	12 mm
長度 (毫米)	179 mm
Construction length	178.00 mm
Technical - Lifespan	
Rated lamp life time	5000 h
Nominal lamp life time	5000 h
Rated lamp survival factor 2000 h	0.99
Rated lamp survival factor 4000 h	0.99
Rated lamp survival factor 6000 h	0.97
Rated lamp survival factor 8000 h	0.85
Technical - Light Technical Data	
Rated color rendering index (Ra)	80-89
Nominal luminous flux	820 lm
Rated luminous flux	820 lm
流明輸出 (流明)	820 lm

顯色性	840
Rated color temperature	4000 K
顯色指數	≥ 80
根據EN1264-1的光色	LUMILUX Cool White
Rated LLMF at 2000 h	0.85
Rated LLMF at 4000 h	0.78
Rated LLMF at 6000 h	0.76
Rated LLMF at 8000 h	0.76
顯色級別	1B
色溫 (開)	4000 K

Technical – Temperatures	
Rated ambient temp.w.max.luminous flux	25.0 °C

包裝種類舉例				
EAN	包裝單位 個/ 單位	尺寸規格 (高 x 寬 x 長)	毛重	體積
4050300010601	Folding carton box (內裝 1 Piece)	40,000 公釐 x 25,000 公釐 x 187,000 公釐	41,100 克 (55,000 克)	0,187 立方公 寸
4050300240848	Shipping carton box (內裝 50 Piece)	206,000 公釐 x 191,000 公釐 x 241,000 公釐	2,925 公斤 (2,750 公斤)	9,482 立方公 寸

Their small dimensions and slim design make OSRAM DULUX S lamps ideal for creative lighting.

- Single-ended plug-in base G23 with integrated starter and RF suppression capacitor
- The colored version is ideal for cost-effective creative illumination and decoration

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)