

Sunon General DC Brushless Fan

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

40x40x10 mm



Model	P/N	Bearing ● Sleeve ○ BALL ● 2BALL	Rating Voltage (VDC)	Power Current (AMP)	Power Consumption (WATTS)	Speed (RPM)	Air Flow (CFM)	Static Pressure (Inch-H ₂ O)	Noise (dBA)	Weight (g)
KD0504PFB1-8	OC	○	5	0.11	0.6	7500	7.5	0.17	28	16
KD0504PFB2-8	OC	○	5	0.09	0.5	6500	6.5	0.15	26	16
KD0504PFB3-8	OC	○	5	0.07	0.35	5300	4.6	0.105	23.5	16
KD0504PFS1-8	OC	●	5	0.11	0.6	7000	7	0.16	27	16
KD0504PFS2-8	OC	●	5	0.10	0.5	6000	5.9	0.14	25	16
KD0504PFS3-8	OC	●	5	0.07	0.35	4500	4.5	0.09	22.8	16



Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
* KD1204PFBX	11	○	12	0.14	1.7	9000	10	0.25	40	14
* KD1204PFB1	11	○	12	0.11	1.3	7500	8.5	0.19	35	14
* KD1204PFB2	11	○	12	0.09	1.1	6500	7.5	0.15	30	14
* KD1204PFSX	11	●	12	0.14	1.7	8500	9.5	0.25	39	14
* KD1204PFS1	11	●	12	0.11	1.3	7000	8	0.18	33	14
* KD1204PFS2	11	●	12	0.09	1.1	5800	7	0.12	28	14

40x40x20 mm



Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
KD0504PKB2		○	5	0.21	1.0	6500	7	0.16	29	27
KD0504PKB3		○	5	0.14	0.7	5300	6.2	0.12	24	27
KD0504PKS2		●	5	0.21	1.0	6000	6.5	0.12	25.5	27
KD0504PKS3		●	5	0.14	0.7	4500	5.2	0.08	22.8	27
KD2404PKB2		○	24	0.04	1.0	6500	7	0.16	29	27
KD2404PKB3		○	24	0.03	0.7	5000	6	0.11	24	27
KD2404PKS2		●	24	0.05	1.2	6000	6.5	0.12	25.5	27
KD2404PKS3		●	24	0.03	0.7	4500	5.2	0.08	22.8	27



Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
KD1204PKB1	H	○	12	0.10	1.2	7400	9.1	0.22	27	28
KD1204PKB2	H	○	12	0.07	0.8	6500	8	0.17	22.5	28
KD1204PKB3	H	○	12	0.05	0.6	5400	6.5	0.12	19	28
KD1204PKS1	H	●	12	0.10	1.2	7200	8.9	0.21	25.5	28
KD1204PKS2	H	●	12	0.07	0.8	6200	7.7	0.16	21	28
KD1204PKS3	H	●	12	0.06	0.7	5200	6.3	0.11	18	28

45x45x10mm



Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
KD0545PFB1-8	OC	○	5	0.12	0.6	6300	9	0.16	29	20
KD0545PFB2-8	OC	○	5	0.10	0.5	5500	7.5	0.12	28	20
KD0545PFB3-8	OC	○	5	0.07	0.35	4500	6.2	0.10	26	20
KD0545PFS1-8	OC	●	5	0.12	0.6	6000	8	0.14	28.5	20
KD0545PFS2-8	OC	●	5	0.10	0.5	5000	6.8	0.10	27	20
KD0545PFS3-8	OC	●	5	0.07	0.35	4000	5.5	0.07	23	20



Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
* KD1245PFB1	11	○	12	0.15	1.8	7300	13	0.22	37	15
* KD1245PFB2	11	○	12	0.12	1.4	6500	11.5	0.18	35	15
* KD1245PFB3	11	○	12	0.10	1.2	5600	10.3	0.12	30	15
* KD1245PFS1	11	●	12	0.15	1.8	7100	12.5	0.21	36	15
* KD1245PFS2	11	●	12	0.12	1.4	6000	11	0.16	33	15
* KD1245PFS3	11	●	12	0.10	1.2	5000	9.2	0.11	28	15

* :2003 new product.

*Specifications subject to change without notice.