

【商品名稱：】OK KYNAR 鍍銀線



【商品簡介：】專供電信繞線與治具接線用

KYNAR 鍍銀線規格表

線徑 Wire	內徑 Size	外徑 Insulation	藍色(blue) 長度-英尺(ft.) Length in Feet		黑色(black) 長度-英尺(ft.) Length in Feet		棕色(brown) 長度-英尺(ft.) Length in Feet		綠色(green) 長度-英尺(ft.) Length in Feet		灰色(gray) 長度-英尺(ft.) Length in Feet	
AWG	mm	mm	B	B	BLK	BLK	BRN	BRN	GRN	GRN	GRY	GRY
R-24	0.50	0.76	500	10,000	500	10,000	500	10,000	500	10,000	N/A	N/A
R-26	0.40	0.70	1,000	10,000	1,000	10,000	1,000	10,000	1,000	10,000	N/A	N/A
R-28	0.32	0.60	1,000	20,000	1,000	20,000	1,000	20,000	1,000	20,000	N/A	N/A
R-30	0.25	0.50	1,000	20,000	1,000	20,000	1,000	20,000	1,000	20,000	N/A	N/A

線徑 Wire	內徑 Size	外徑 Insulation	橘色(orange) 長度-英尺(ft.) Length in Feet		紅色(red) 長度-英尺(ft.) Length in Feet		紫色(violet) 長度-英尺(ft.) Length in Feet		白色(white) 長度-英尺(ft.) Length in Feet		黃色(yellow) 長度-英尺(ft.) Length in Feet	
AWG	mm	mm	ORG	ORG	R	R	V	V	W	W	Y	Y
R-24	0.50	0.76	500	10,000	500	10,000	N/A	N/A	500	10,000	500	10,000
R-26	0.40	0.70	1,000	10,000	1,000	10,000	1,000	10,000	1,000	10,000	1,000	10,000
R-28	0.32	0.60	1,000	20,000	1,000	20,000	1,000	20,000	1,000	20,000	1,000	20,000
R-30	0.25	0.50	1,000	20,000	1,000	20,000	1,000	20,000	1,000	20,000	1,000	20,000

詳細說明：

OK KYNAR 鍍銀線

KYNAR 是美國 Penn Walt 公司發展出來的一種高級絕緣材料，使用在電線絕緣上具有許多特性。

特性：

- 絕緣皮非常薄，不佔空間
- 耐高溫達 105 °C
- 韌性高，非常不容易破裂
- 延展性高，非常不容易拉斷

適用範圍：

- 繞接 (WIRE WRAPPING) 用
- 製作測試治具 (TESTING FIXTURES)
- 耐高溫線路接線用

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)