

Digital Thermometers (TM-36x)



FEATURES:

- **Dual Display.(LCD 18.2mm)**
- **Resolution: 0.1°C/0.1°F(below 1000°C)**
- **Function: °C/°F,MAX/MIN,HOLD,REL, MEM,LIMIT,HI/LO,TYPE,T1-T2.**
- **MEM--to save 10 data.**
- **Auto Power OFF.**
- **Low Battery indication.**
- **CE-Mark approval.Conform to ITS-90.**

ORDERING INFORMATION:

TM-36□ SERIES

- 1--Single Channel K Type
- 2--Single Channel K/J Types
- 3--Dual Channel K Type
- 4--Dual Channel K/J Types

Measurement: TC	K Type: -200°C ~ 1372°C (-328°F ~ 2501°F) J Type: -210°C ~ 1200°C (-346°F ~ 2192°F) T Type: -250°C ~ 400°C (-418°F ~ 752°F) E Type: -210°C ~ 1000°C (-346°F ~ 1832°F)
Accuracy:	±(0.1% reading+0.7°C), ±(0.1% reading+1.4°F)
Operation Temperature and humidity:	0°C ~ 50°C : 0 ~ 80%RH
Storage Temperature and humidity:	-10°C ~ 60°C : 0 ~ 80%RH
Power requirement:	R03(AB) / SIZE AAA / 1.5V / UM-4 X 4PCS
Input protection at thermocouple input:	AC/DC 24Vrms.
Dimension: (Indication Hoster)	125mm(L)x 82mm(W)x 43mm(T).
Weight: (Indication Hoster)	APPROX:350g

高精準迷你多功能溫度錶 TM-361~364

特點：

- 四位超大液晶雙顯示(18.2mm)
- 高精準度±0.1%讀值+0.7°C)
- 高解析度，快速反應，T1/T2 雙顯示
- 測量範圍：K Type-200~1372°C
J Type-210~1200°C
- MEM-可紀錄 10 組資料並可呼叫刪除
- 功能設定：最大，最小，讀值鎖定，記憶，相對值，攝氏，華式溫度，
T1 減 T2，溫度形式，最高/最低溫度設定/警報
- 電源自動關機及解除，低電力警示
- CE-認證通過，符合 ITS-90
- 外觀尺寸(不含保護套)：106(L)x74(W)x33(T)mm
- 重量：約 350 公克(含保護套，電池)

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)