

HOOK UP WIRE**UL Style 1011*, 1015, 1028, 1283 VW-1 105°C 600 Volts****CSA TEW, 105°C**

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Product Construction**Conductor:** - 24 thru 6 AWG

- Solid, Stranded or Topcoat, Bare or Tinned Copper conductor per ASTM B-33

Insulation: - Color coded PVC, Temperature: -40°C to +105°C (*UL1011 -40°C to +80°C)

UL Style	AWG/ Strand	Cond. Type	Nom. Insul Wall and Type	Nom. O.D.		Color Code
1011	18 (41x34)	Bare Copper	.030" PVC	.105		0
1015	24 (solid)	Tin Copper	.032" PVC	.083		0-9
1015	22 (solid)	Tin Copper	.032" PVC	.093		0-9
1015	20 (solid)	Tin Copper	.032" PVC	.098		0-9
1015	18 (solid)	Tin Copper	.032" PVC	.104		0-9
1015	26 (7x34)	Tin Copper	.032" PVC	.083		0-9
1015	24 (7x32)	Tin Copper	.032" PVC	.087		0-9
1015	22 (7x30)	Tin Copper	.032" PVC	.093		0-9
1015	22 (7x30)	Topcoat	.032" PVC	.095		0-9
1015	20 (10x30)	Tin Copper	.032" PVC	.100		0-9
1015	20 (10x30)	Topcoat	.032" PVC	.102		0-9
1015	18 (16x30)	Tin Copper	.032" PVC	.109		0-9
1015	18 (7x26)	Topcoat	.032" PVC	.114		0-9
1015	16 (26x30)	Tin Copper	.032" PVC	.122		0-9
1015	14 (41x30)	Tin Copper	.032" PVC	.139		0-9
1015	12 (65x30)	Tin Copper	.032" PVC	.157		0-9
1015	10 (105x30)	Tin Copper	.032" PVC	.187		0-9
1028	8 (133x29)	Tin Copper	.048" PVC	.262		0,2,5,9
1283	6 (133x27)	Tin Copper	.064" PVC	.330		0,2,5,9

Packaging: Hook Up Wire**Industry Approvals: Hook UP Wire**

- 1000 ft. spools
- 100 ft. spools
- Also available on bulk reels
- UL style 1011
- UL style 1015
- UL style 1028
- UL style 1283
- CSA-TEW
- Passes UL VW-1 flame test
- OSHA acceptable

Applications: Hook Up Wire

- Appliance wiring
- Point to point wiring
- Internal wiring of meters, panels, electrical and electronic equipment

Hook Up Wire Color Codes

0	Black	4	Yellow	8	Gray
1	Brown	5	Green	9	White
2	Red	6	Blue		
3	Orange	7	Violet		

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)